



.XX ±0.13 .XXX ±0.05

$\land \neg$	
$X \mid \Box \mid$	OF

ISSUE NUMBER
RIGINAL

(1)






NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

-55°C ~ 125°C

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED COPPER ALLOY, 30µ" GOLD PLATED




POWER/CO-AX CONTACT RATING:	20A (CURRENT)
(IF PRESENT)	
SIGNAL CONTACT CURRENT RATING:	5A PER CONTACT
SIGNAL CONTACT RESISTANCE:	10mΩ MAX.
	5000M0 min

**INSULATOR RESISTANCE:** DIELECTRIC WITHSTANDING VOLTAGE:


**OPERATING TEMPERATURE:** 

5000MΩ min.

1000V AC rms



			SW REFERENCE NO.: 629 COMBO ASSEMBLY		
			DRAWN: C.B	DATE: JAN. 01/20	19
			CHECKED:	DATE:	
EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2	
	YOUR CONNECTION TO QUALITY & SERVICE	MANUFACTURE OR SALE OF APPARATUS	DRAWING NUMBER: 629-17	V2640-2N4	ISSUE
YOUR CONNECTION TO			PART NUMBER: 629-17	V2640-2N4	1





THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

