

C0805X222M1RAC3316

SMD Auto X7R VW80808, Ceramic, 2200 pF, 20%, 100 VDC, X7R, SMD, MLCC, Automotive Grade, 0805



Click here for the 3D model.

Dimensions	
Chip Size	0805
L	2mm +/-0.3mm
W	1.25mm +/-0.3mm
Т	0.78mm +/-0.20mm
S	0.75mm MIN
В	0.5mm +/-0.25mm

Packaging Specifications	
Packaging	T&R, 180mm, Plastic Tape
Packaging Quantity	4000

Series SMD Auto X7R VW80808 Style SMD Chip Description SMD, MLCC, Automotive Grade Features VW 80808 Specification Compliant RoHS Yes Termination Flexible Termination Failure Rate N/A Qualifications AEC-Q200	General Information	
Description SMD, MLCC, Automotive Grade Features VW 80808 Specification Compliant RoHS Yes Termination Flexible Termination Failure Rate N/A	Series	SMD Auto X7R VW80808
Features VW 80808 Specification Compliant RoHS Yes Termination Flexible Termination Failure Rate N/A	Style	SMD Chip
RoHS Yes Termination Flexible Termination Failure Rate N/A	Description	SMD, MLCC, Automotive Grade
Termination Flexible Termination Failure Rate N/A	Features	VW 80808 Specification Compliant
Failure Rate N/A	RoHS	Yes
1,471	Termination	Flexible Termination
Qualifications AEC-Q200	Failure Rate	N/A
	Qualifications	AEC-Q200
AEC-Q200 Yes	AEC-Q200	Yes
Shelf Life 152 Weeks	Shelf Life	152 Weeks

Specifications	
Capacitance	2200 pF
Capacitance Tolerance	20%
Voltage DC	100 VDC
Dielectric Withstanding Voltage	250 VDC
Temperature Range	-55/+125°C
Temperature Coefficient	X7R
Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC)	15%, 1kHz 1.0Vrms
Dissipation Factor	2.5% 1 kHz 1.0Vrms
Insulation Resistance	100 GOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.