



Click [here](#) for the 3D model.

### Dimensions

|    |                 |
|----|-----------------|
| L  | 18mm -0.5mm     |
| H  | 19mm -0.5mm     |
| T  | 11mm -0.5mm     |
| S  | 15mm +/-0.4mm   |
| LL | 4mm +2mm        |
| F  | 0.8mm +/-0.05mm |
| G  | 0.5mm NOM       |

### Packaging Specifications

|                    |           |
|--------------------|-----------|
| Packaging          | Bulk, Bag |
| Packaging Quantity | 450       |

### General Information

|                  |   |
|------------------|---|
| Series           | F462  |
| Dielectric       | Metallized Polypropylene  |
| Style            | Radial  |
| Features         | MKP, Pulse  |
| RoHS             | Yes   |
| Lead             | Cut/Short   |
| AEC-Q200         | No  |
| Component Weight | 4.927 g   |
| Miscellaneous    | The Rated Voltage Decreases 2%/C Between +85C And +105C (1.25%/C For AC). ClimCat: 55/105/56. |
| Notes            | Series Replaced by R75.   |

### Specifications

|                       |                          |
|-----------------------|--------------------------|
| Capacitance           | 0.15 uF                  |
| Capacitance Tolerance | 5%                       |
| Voltage AC            | 300 VAC                  |
| Voltage DC            | 1000 VDC, 600 VDC (105C) |
| Temperature Range     | -55/+105°C               |
| Rated Temperature     | 85°C                     |
| Dissipation Factor    | 0.05% 1kHz, 0.06% 10kHz  |
| Insulation Resistance | 100 GOhms                |
| Max dV/dt             | 1600 V/us                |
| Inductance            | 6 nH                     |