


FMROV104ZF-L1

FMR, Supercapacitors, Radial Molded, 0.1 F, -20/+80%, 3.5 VDC, Bent, Lead Spacing = 5mm



General Information	
Series	FMR
Description	Radial Molded Double Layer Capacitor
RoHS	Yes
AEC-Q200	No
Component Weight	1.6 g

Specifications	
Capacitance	0.1F
Capacitance Tolerance	-20/+80%
Voltage DC	3.5 VDC
Temperature Range	-40/+85°C
Rated Temperature	85°C
Resistance	50000 mOhms (1kHz)
Discharge Current	0.09 mAmps (30 Minutes After Charging)

Click here for the 3D model.

Dimensions	
W	10.5mm +/-0.5mm
н	11.5mm +/-0.5mm
Т	6.5mm +/-0.5mm
S	5mm +/-0.5mm
G	0.4mm +/-0.1mm
LT1	0.5mm +/-0.1mm
LT2	0.4mm +/-0.1mm

Packaging Specifications		
Lead	Bent	
Packaging	Bulk, Box	
Packaging Quantity	800	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.