

Specification Sheet

Part Number: 558-00358



Adhesive Labels, Solid Color Continuous Roll, 4.0" x 250', VL, Yellow, 250ft/roll

Article Number	558-00358
Туре	HT4YE250
Color	Yellow (YE)
Features & Benefits	• Pre-printed header striped continuous vinyl rolls come in different header colors, providing a variety of printing options. • The headers can be printed with various ARC FLASH, WARNING And CAUTION headlines to meet OSHA safety standards for identifying electrical panels and equipment. • Signs can be designed in Tagprint Pro labeling software and printed with any HellermannTyton thermal transfer printing system with optional cutter attached.
Quantity Per	roll

Product Description	Continuous Vinyl Labels are made with UV-stable materials for long outdoor life. The labels are extruded in the actual color and not colored using surface inks for long-term fade resistance. Vinyl labels are provided in continuous rolls so that the markers can be printed and cut to any length using HellermannTyton thermal transfer printing systems. Good for all surface types except powder coat painted or low surface energy substrates such as polyproylene. Test on these surfaces before approving.
Short Description	Adhesive Labels, Solid Color Continuous Roll, 4.0" x 250', VL, Yellow, 250ft/roll
Global Part Name	HT4YE250-V-YE
Technical Description	Solid Colored Continuous Roll, 4.0" X 250', Yellow
Length L (Imperial)	250.0
Length L (Metric)	76.20
Variant	3.2mil, 50lb bleached kraft paper
Width W (Imperial)	4.0
Width W (Metric)	101.6
Width of Liner (Metric)	101.6
Width of Liner (imperial)	4.0

Material V	'inyl
-------------------	-------

Adhesive	Acrylic
Halogen free	No
UV Resistant (Yes/No)	Yes
Adhesive Operating Temperature	-40°F to +180°F (-40°C to +82°C)
Operating Temperature (Metric)	-40°F to +180°F (-40°C to +82°C)
ROHS Complaint	Yes
Certification/Specification WEB	UL 969
Package Quantity(Imperial)	250
Package Quantity (Metric)	76.20
Customs Number	3919102055
Labels per Column	1
Labels per Row	1
Weight (Metric)	2.04
Weight (Imperial)	4.50

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions