

THIS IS A C.A.D. GENERATED DRAWING TOLERANCE UNLESS OTHERWISE SPECIFIED DO NOT MAKE MANUAL REVISIONS TO MASTER.




ISSUE NUMBER		
ORIGINAL		

(1)







NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

COPPER ALLOY, GOLD FLASH PLATED **OPERATING TEMPERATURE:** -55°C ~ 125°C

.X ±0.25 .XX ±0.13 .XXX ±0.05

POWER/CO-AX CONTACT RATING: (IF PRESENT) SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE: $10m\Omega$ MAX.

INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE: 20A (CURRENT)

5000MΩ min.

1000V AC rms

STEEL, TIN PLATED

THERMOPLASTIC POLYESTER, UL94V-0

	COMBINATION D-SUB		SW REFERENCE NO.: 629 COMBO ASSEMBLY			
			DRAWN: C.B	DATE: JAN. 01/20	19	
			CHECKED:	DATE:		
	EDAG INC TORONTO, ONTARIO CANADA	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2	
			DRAWING NUMBER: 629-2WK	2250-2TB	ISSUE	
			PART NUMBER: 629-2WK	2250-2TB	1	



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.



REFERENCE NO.: 629 COMBO ASSEMBLY				
AWN: C.B	DATE: JAN. 01/2019			
IECKED:	DATE:			
ALE: (IN C.A.D. 1:1)	SHEET 1 OF 2			
AWING NUMBER: 629-2W	K2250-2TB ISSUE			
RT NUMBER: 629-2W	(2250-2TB 1			
	· · · · · · · · · · · · · · · · · · ·			

