т радование и справо с справо						
A		4				
	LAYOUT SHOWN AS EXAMPLE	3				
Keying Shown as example						
CHARACTERISTICS Connector dimension -Standard : Based on MIL-DTL-38999 Series III Dim Nominal						
Shell Material Aluminium		\vdash				
-Shell Plating : Olive drab Cadmium VV THREAD M25x1-6g	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with					
-Insulator : Thermoplastic	sulator : Thermoplastic the Specifications issued by either of the Parties or by a third party					
-Contacts : Copper Alloy	(professional recommendation, technical notice.)					
-Seals & Grommet : Silicon Elastomer	Country Jurisdiction & Control List					
Contact Plating : Gold over copper Alloy 0.8μm minimum	FR Not Listed					
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories	PN: 8D517W22SN					
-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours	A 17-10-2016 First Release					
	ISS DATE Latest modification - by MOD N°	-				
	Designed By: Date: CUSTOMER DRAWING					
	TITLE Aluminium Plug 8D series					
→ BASIC SERIES: 8D 5 - 17 W 22 S N → SHELL TYPE : Plug with RFI Shielding	SCALE General linear NPRDS / PROJECT NA Image: scale s					
	This document is the property of	-				
CONTACT TYPE : Standard Crimp Contact ORIENTATION SHELL SIZE : 17 CONTACT TYPE : SOCKET(500 Matin						
PLATING : W = Olive drab Cadmium CONTACT LAYOUT : 17						
H I G I F I E	D C B A					

	工	۵	п –	m		0
4		Contact Layout 22				
	Ctc A B C D	2#12 2#8 Triax 17-22 X Y 0 4.57 6.32 0 0 -4.57 -6.32 0				
	-					SOURIAU shall not be liable for ar due to a use of the Products w the Specifications issued by either o (professional recommenda
N						Count FR PN: 8D517
					ISS DATE Designed By:	Date:
-					SCALE NA	Alumir General linear Tolerances: ±
	Н	G	F	E	FORMAT A3	WWW.SOURIAU.C SOURIAU 8D517W C

