


ODL2.5



ODL2.5(I.S)



ODLG2.5



ODLG2.5(I.S)



Dimensions & Weight

Width	5 mm	5 mm	5 mm	5 mm
Length	62.0 mm	62.0 mm	62.0 mm	62.0 mm
Height w DIN Rail	35 x 7.5 mm 35 x 15 mm	63.0 mm 70.5 mm	63.0 mm 70.5 mm	63.0 mm 70.5 mm
Weight per piece	13.0 g	14.2 g	15.3 g	17.0 g

Technical Data/Ratings

Approvals								
Wire Size (solid / stranded)	24-12 AWG	0.2-2.5 mm ²	24-12 AWG	0.2-2.5 mm ²	24-12 AWG	0.2-2.5 mm ²	24-12 AWG	0.2-2.5 mm ²
Voltage Rating	300 V	800 V AC/DC	300 V	800 V AC/DC	300 V	800 V AC/DC	300 V	800 V AC/DC
Current Rating	25 A	24 A	25 A	24 A	25 A	24 A	-	-
Torque	4.5 lb-in	0.4 Nm	4.5 lb-in	0.4 Nm	4.5 lb-in	0.4 Nm	4.5 lb-in	0.4 Nm
Insulation Material	Polyamide 66		Polyamide 66		Polyamide 66		Polyamide 66	

Installation Instructions

Wire Stripping Length	8 mm	8 mm	8 mm	8 mm
Screwdriver	Flat Head 0.6 x 3.5 mm	Flat Head 0.6 x 3.5 mm	Flat Head 0.6 x 3.5 mm	Flat Head 0.6 x 3.5 mm

Terminal Blocks

Grey Stackable Clip-on							
Red R							
Blue BU							
Black BL							
Orange O							
Green G							
Yellow Y							
White W							

	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
ODL2.5	ODL2.5	50	ODL2.5(I.S)	ODL2.5(I.S)	50	ODLG2.5	ODLG2.5	50
ODL2.5A	ODL2.5A	50	ODL2.5A(I.S)	ODL2.5A(I.S)	50	ODLG2.5A	ODLG2.5A	50
ODL2.5/R	ODL2.5/R	50	ODL2.5/R	ODL2.5/R	50	-	-	-
ODL2.5/BU	ODL2.5/BU	50	ODL2.5/BU	ODL2.5/BU	50	-	-	-
ODL2.5/BL	ODL2.5/BL	50	ODL2.5/BL	ODL2.5/BL	50	-	-	-
ODL2.5/O	ODL2.5/O	50	ODL2.5/O	ODL2.5/O	50	-	-	-
ODL2.5/G	ODL2.5/G	50	ODL2.5/G	ODL2.5/G	50	-	-	-
ODL2.5/Y	ODL2.5/Y	50	ODL2.5/Y	ODL2.5/Y	50	-	-	-
ODL2.5/W	ODL2.5/W	50	ODL2.5/W	ODL2.5/W	50	-	-	-

Accessories

	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
End Plate	EP0DL2.5	50	EP0DL2.5	50	EP0DL2.5	50	EP0DL2.5	50
Front Side	EP10DL2.5	50	EP10DL2.5	50	EP10DL2.5	50	EP10DL2.5	50
Back Side								
DIN Rail	2511120	20	2511120	20	2511120	20	2511120	20
35mm	CA701-15/S	20	CA701-15/S	20	CA701-15/S	20	CA701-15/S	20
35mm								
End Stop	CA702	50	CA702	50	CA702	50	CA702	50
	CA802	50	CA802	50	CA802	50	CA802	50
	CA202	25	CA202	25	CA202	25	CA202	25
Shorting Link/Jumpers	JX2.5/2	100	JX2.5/2	100	JX2.5/2	100	JX2.5/2	100
2 pole	JX2.5/3	50	JX2.5/3	50	JX2.5/3	50	JX2.5/3	50
3 pole	JX2.5/4	50	JX2.5/4	50	JX2.5/4	50	JX2.5/4	50
4 pole	JX2.5/5	50	JX2.5/5	50	JX2.5/5	50	JX2.5/5	50
5 pole	JX2.5/6	10	JX2.5/6	10	JX2.5/6	10	JX2.5/6	10
6 pole	JX2.5/7	10	JX2.5/7	10	JX2.5/7	10	JX2.5/7	10
7 pole	JX2.5/8	10	JX2.5/8	10	JX2.5/8	10	JX2.5/8	10
8 pole	JX2.5/10	10	JX2.5/10	10	JX2.5/10	10	JX2.5/10	10
10 pole								
Marking Tag	MT5	1 Pk. (100 tags)	MT5	1 Pk. (100 tags)	MT5	1 Pk. (100 tags)	MT5	1 Pk. (100 tags)