

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
A	1	ECR-18-004585	26MAR2018	DW	CW
B	1	ECR-19-006038	14MAY2019	BS	CW
C	1	ECR-21-117384	15NOV2021	WQR	CW
C1	1	ECR-22-161571	03JAN2023	WQR	CW

NOTES:

- TECHNICAL CHARACTERISTICS:
INSULATION MATERIAL: PC (GRAY)
RATED VOLTAGE: 250V
RATED CURRENT: 10A
INSULATION RESISTANCE: $\geq 400M\Omega$
RATED IMPULSE VOLTAGE: 4KV
POLLUTION DEGREE: 3
FLAMMABILITY: UL94V-0
MATING CYCLES: 500 CYCLES
WIRE RANGE: $0.14mm^2 \sim 2.5mm^2$ (AWG26-AWG14)
CONTACT TYPE: CRIMP CONTACT
- CONTACT NEED TO BE ORDERED SEPARATELY.
(ORDER NO. REFER TO DRAWING: T20200X20XX000.)

注释:

- 技术参数:
绝缘材料: PC (GRAY)
额定电压: 250V
额定电流: 10A
绝缘电阻: $\geq 400M\Omega$
脉冲电压: 4KV
污染等级: 3
阻燃等级: UL94V-0
插拔次数: 500次
接线范围: $0.14mm^2 \sim 2.5mm^2$ (AWG26-AWG14)
接线类型: 冷压接
- 端子需要单独订购.
(订购单号参考图面:T20200X20XX000.)

SCALE 1:1

SCALE 1:1

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:	TOLERANCES UNLESS OTHERWISE SPECIFIED:
mm	
	0 PLC ±-
	1 PLC ±-
	2 PLC ±-
	3 PLC ±-
	4 PLC ±-
	ANGLES ±
MATERIAL	FINISH
-	-
-	-

DWN	13OCT2016
CHK	CHARLIE.HU
APVD	13OCT2016
CHK	KYLE.ZENG
APVD	13OCT2016
CHK	CHRIS.WANG
PRODUCT SPEC	108-137116
APPLICATION SPEC	114-137116
WEIGHT	-
CUSTOMER DRAWING	

T2080172201-000		HQ-017-F	HQ-017 FEMALE INSERT HQ-017母插	
PART NUMBER 料号		PART DESCRIPTION 描述		
DWN		TE Connectivity		
CHK		NAME HQ-017-F		
APVD		SIZE	CAGE CODE	DRAWING NO
PRODUCT SPEC		A3	-	©-T2080172201000
APPLICATION SPEC		RESTRICTED TO		-
WEIGHT		SCALE	SHEET	OF
CUSTOMER DRAWING		3:2	1	1
		REV	C1	

1470-19 (3/13)