

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



HEAVYCON EVO panel mounting base, plastic, B10, with single locking latch, height: 30.5 mm, with flat gasket, with protective cover

Your advantages

- Both contact insert PE sheets are connected by means of a metal frame integrated in the sleeve housing
- Metal inlays ensure leading PE contact with angled plugs

- Marking label can be attached



Key Commercial Data

Packing unit	1 pc	
GTIN	4 046356 776950	
GTIN	4046356776950	

Technical data

Dimensions

Height	30.5 mm
Width	53 mm
Length	93.5 mm
Length of the assembly cutout	65 mm
Width of the assembly cutout	35 mm

Ambient conditions

Degree of protection (IP)	IP66 (when plugged in or with locked protective cover)
Degree of protection (NEMA)	12 (UL 50e)



Technical data

Ambient conditions

Ambient temperature (operation)	-40 °C 125 °C

General

Note	For contact inserts HC-B10, BB18, DD42, M, K8/24, HV03-I-PT, HC- 3-EC	
Size	B10	
Housing type	Panel mounting base	
Color	black	
Locking type	with single locking latch	
Torque	0.5 Nm 1.7 Nm (Fixing screws for panel mounting base)	
Screw connection	none	
Protective cover	yes	
Housing material	PA	
Material lock	PA	
Material, protective cover	PA	
Flammability rating according to UL 94	V0	
Assembly instructions	Not for D series terminal adapters	
Connection	Not for HC-B 24-ADP-B adapter plates	

Standards and Regulations


Flammability rating according to UL 94	V0
--	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e	
	No hazardous substances above threshold values	

Drawings


Dimensional drawing



Dimensional drawing



Dimensional drawing



Mounting cutout	
Approvals	
Approvals	
Approvals	
EAC / DNV GL	
Ex Approvals	
Approval details	

EAE

EAC

RU C-DE.Al30.B.01102



Approvals

DNV GL https://approvalfinder.dnvgl.com/ TAE000037S

Phoenix Contact 2019 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com