D I	г	т	D		0	ω		
	ØS							
۵					LAYOUT SHOWN	AS EXAMPLE		
	Keying Shown as	example						
CHARACTERISTICS	 							
-Standard : Based on MIL-DTL-38999 Series III		Connector dimension Dim Nominal						
-Shell Material: AluminiumØS25 Max-Shell Plating: Olive drab CadmiumZ31 Max-Insulator: ThermoplasticVV THREADM15x1-6g-Contacts: Copper Alloy				SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)				
-Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minir							n & Control List ot Listed	
-Contact Plating : Gold over copper Alloy 0.8µm minin -Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories		PN: 8D511W05SD						
-Temperature Range : -65°C to +175°C				A 17-10-2016	First Release			
-Salt Spray : 500 hours 				ISS DATE Designed By:	Latest modification - by Date:		JSTOMER DRAWING	MOD N°
				TITLE		iminium Plug 8D s		
BASIC SERIES: 8D 5 - 11 SHELL TYPE : Plug with RFI Shielding	. W 05 S D			SCALE	General lin Toleranc ±		NPRDS / PROJECT 859	
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11		ORIENT CONTACT TYPE : SOCKET(500		SOURIAU	WWW.SOURIA	U.COM	This document is the prope SOURIAU it must not be reproduced communicated without perr	d or
PLATING : W = Olive drab Cadmium	┘ │ └────	CONTACT TIFE : SOCKET(SOC		FORMAT		AU DRG N°		SHEET
		CONTACT LATO						
				A3	2D51	1W05SD-C		1/2

r	Ŧ	۵	וד	m	D	0
		Contact Layout				
4	- <u>×</u>	$ \begin{array}{c} \bullet \\ \bullet $				
	Conta positio ID A B C C D E Shell Arrangement size no. conta	X-axis (mm)         Y-axis (mm)           +.0.65 (1.65)         +.0.56 (1.42)           +.113 (2.87)        065 (1.65)           +.000 (0.00)        130 (3.30)          113 (2.87)        065 (1.65)          005 (1.65)         +.056 (1.42)           er of         Size         Service         Contact         Supersedes           acts         contacts         rating         location         Supersedes				
ω	11 -5 5	20 I All MS20050-5				
	-					SOURIAU shall not be liable for due to a use of the Products the Specifications issued by eithe
NJ						(professional recommend Cou F PN: 8D511
					A 17-10-20 ISS DATE Designed By:	116 First Release Latest modification - by Date:
_					SCALE NA	Alum General linea Tolerances: ±
					FORMAT A3	U WWW.SOURIAU SOURIA 8D511
L	Н	G	F	E	D	C

