

# Cat6a Pass-Through Cassette - (x12) RJ45

MODEL NUMBER: N484-12RJ











### **Highlights**

- High Density Copper Cassette for use with the N484-00U and N484-01U chassis'
- Cat6a Pass-through Cassette, with (x12) RJ45 connections
- Rated for 10 Gbps Ethernet data transfer speeds

### **Package Includes**

- N484-12RJ Cat6a Pass-Through Cassette - (x12) RJ45
- Quick Start Guide

#### Description

Tripp Lite's N484-12RJ is a High Density Cat6a Pass-through Cassette with (x12) RJ45 connections. Designed specifically for use with Tripp Lite's N484-00U and N484-01U chassis'; up to 4 cassettes per N484-01U, or 1 per N484-00U. Each RJ45 connection is rated for 10 Gbps Ethernet data transfer speeds. Installation is simple, with the cassette being easily installed or removed using screw tabs to lock or unlock it from the panel; no tools required. Furthermore, each cassette features factory terminated connectors that reduce the time and labor required of field connector terminations. Cassette housing is manufactured with heavy duty, 1.0mm Cold Rolled Steel.

#### **Features**

- High Density Copper Cassette for use with the N484-00U and N484-01U chassis'
- Cat6a Pass-through Cassette, with (x12) RJ45 connections
- Rated for 10 Gbps Ethernet data transfer speeds
- Installation is simple, with the cassette being easily installed or removed using screw tabs to lock or unlock it from the panel; no tools required
- Each cassette features factory terminated connectors that reduce the time and labor required of field connector terminations.
- Housing made of heavy duty, 1.0mm Cold Rolled Steel

## **Specifications**

| OVERVIEW |              |
|----------|--------------|
| UPC Code | 037332187222 |
| PHYSICAL |              |





| Shipping Dimensions (hwd / cm)         | 5.99 x 20.07 x 3.71       |  |
|--|---------------------------|--|
| Shipping Dimensions (hwd / in.)        | 2.36 x 7.90 x 1.46        |  |
| Shipping Weight (kg)                   | 0.23                      |  |
| Shipping Weight (lbs.)                 | 0.51                      |  |
| ENVIRONMENTAL                          |                           |  |
| Operating Temperature Range            | -4 to 122 F (-20 to 50 C) |  |
| CONNECTIONS                            |                           |  |
| Ports                                  | 12                        |  |
| Side A - Connector 1                   | RJ45 (FEMALE)             |  |
| Side B - Connector 1                   | RJ45 (FEMALE)             |  |
| FEATURES & SPECIFICATIONS              |                           |  |
| Technology                             | Cat6a                     |  |
| CERTIFICATIONS                         |                           |  |
| Approvals                              | RoHS, REACH               |  |
| WARRANTY                               |                           |  |
| Product Warranty Period<br>(Worldwide) | Lifetime limited warranty |  |

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>