

# Data sheet

## 2092.0 TS 15 GL



DIN rail, slotted, Width: 15 mm, Height: 5.5 mm, Material: Steel, Colour: natural

### Business data

Article number	<u>2092.0</u>
Article name	TS 15 GL
GTIN (EAN)	4044211049003
Colour	Natural
Packaging unit	40
Quantity unit	M
Weight per piece (not including packaging)	150 g
Weight per piece (including packaging)	150 g
Unit of weight	G
Customs number	72166190
Country of origin	DE
Product description	DIN rail

### Technical data

#### Dimensions

Length	2000 mm
Hole length	12 mm
Width	15 mm
Hole width	4.2
Height	5.5 mm
Hole spacing (mid-point to mid-point)	20 mm
Thickness	1 mm
Shape of hole	Slotted hole
Slotted hole	✓
Slotted	✓

#### Ratings

Max. short-circuit current	1.2 kA
Max. allowed thermal rated current with PEN function	The usage of protective earth steel busbars is not permitted for PEN functionality! A
Short-circuit resistance I <sub>p</sub>	10 kA

#### Materials

Material	Steel
Surface	Galvanized, thick-film passivated

#### Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2022-06-10
REACH Candidate Substance Note	No
RoHS Conform	yes

---

### Approvals

---

#### Standards and regulations

---

Standards / specifications	DIN EN 60715
----------------------------	--------------

---

#### VDE approval

---

VDE approval	Acc. DIN VDE 0611-3
--------------	---------------------

---



# Data sheet

## 2092.0 TS 15 GL

---

### Media

---



---

**Accessories**

---