## PRODUCT DATASHEET

C17270\_STRADELLA-8-5050-HB-W-PC

### STRADELLA-8-5050-HB-W-PC

~90° beam. Variant from PC.

#### **SPECIFICATION:**

Dimensions 49.5 x 49.5 mm
Height 5 mm
Fastening screw
ROHS compliant yes 1



#### **MATERIALS:**

ComponentTypeMaterialColourFinishSTRADELLA-8-5050-HB-W-PCMulti-lensPCclear

#### **ORDERING INFORMATION:**

 Component
 Qty in box
 MOQ
 MPQ
 Box weight (kg)


 C17270\_STRADELLA-8-5050-HB-W-PC
 800
 160
 4.7

» Box size: 480 x 280 x 300 mm



# **PRODUCT**

## C17270\_STRADELLA-8-5050-HB-W-PC



See also our general installation guide: www.ledil.com/installation\_guide

# PRODUCT DATASHEET

## C17270\_STRADELLA-8-5050-HB-W-PC


### **OPTICAL RESULTS (SIMULATED):**



LED J Series 3030  $\mathsf{FWHM}\,/\,\mathsf{FWTM}$ 89.0° / 109.0° Efficiency 88 %

Peak intensity 0.5 cd/lm LEDs/each optic Light colour White

Required components:




#### LUMILEDS

LED LUXEON 5050 HE FWHM / FWTM 86.0° / 110.0°

Efficiency 86 % Peak intensity 0.5 cd/lm LEDs/each optic 1 White Light colour

Required components:

Protective plate, glass




### LUMILEDS

LED LUXEON 5050 HE

 $\mathsf{FWHM}\,/\,\mathsf{FWTM}$ 88.0° / 110.0° Efficiency 92 %

Peak intensity 0.6 cd/lm LEDs/each optic 1 Light colour White

Required components:




## LUMILEDS

Required components:

LED LUXEON 5050 Square LES

FWHM / FWTM 86.0° / 109.0° Efficiency 88 % Peak intensity 0.5 cd/lm LEDs/each optic White Light colour



Published: 13/12/2019

### **OPTICAL RESULTS (SIMULATED):**


#### OSRAM Opto Semiconductors

LED OSCONIQ C 2424 FWHM / FWTM 80.0° / 106.0°

Efficiency 92 %
Peak intensity 0.6 cd/lm

LEDs/each optic 1
Light colour White

Required components:




## **SAMSUNG**

LED LM301B FWHM / FWTM 91.0° / 110.0°

Efficiency 88 %
Peak intensity 0.5 cd/lm
LEDs/each optic 1
Light colour White

Required components:



# PRODUCT DATASHEET C17270\_STRADELLA-8-5050-HB-W-PC

#### **GENERAL INFORMATION:**

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

#### **MATERIALS:**

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

#### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### **LEDIL Oy**

Joensuunkatu 13 FI-24240 SALO Finland

#### LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

## Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405 , Block B Casic Motor Building Shenzhen 518057 P.R.CHINA

## Local sales and technical support

www.ledil.com/ where\_to\_buy

#### **Shipping locations**

Salo, Finland Hong Kong, China

#### **Distribution Partners**

5/5

www.ledil.com/ where\_to\_buy