

## Fuse - SI FORM C 30 A DIN 72581 - 0913760

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Flat-type plug-in fuse, type C, color code: light green, nominal current: 30 A

### Your advantages

- ✓ With snap-in foot for secure pre-assembly on the PCB
- ✓ Fuse holder for flat-type fuses with a maximum nominal voltage of 32 V

### Key Commercial Data

Packing unit	50 pc
GTIN	 4 017918 104009
GTIN	4017918104009

### Technical data

#### General

Color	light green
Flammability rating according to UL 94	V0

#### Dimensions

Width	5 mm
Length	19 mm

#### General

Fuse	C
Nominal current $I_N$	30 A
Nominal voltage $U_N$	24 V

### Standards and Regulations

Flammability rating according to UL 94	V0
--	----

## Fuse - SI FORM C 30 A DIN 72581 - 0913760

### Approvals

Approvals

---

Approvals

EAC / EAC


---

Ex Approvals

---

### Approval details

EAC		EAC-Zulassung
-----	---	---------------

EAC		RU C- DE.A*30.B.01742
-----	--	--------------------------

---

Phoenix Contact 2019 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>