


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	NOTES
1	50-00425	Connector, plug, USB A	1	
2	50-00030	Connector, dc plug, 2.35x0.7xL20.8 mm, EIAJ-1, molding style, spring contacts	1	
3	30-00008	Wire, 2C BC, 22 AWG, UL2468, 300V, 80C, 3.6 mm, PVC, 87A	1	
4	24-00023	Overmold, PVC, black	1	
5	24-00047	Overmold, PVC, black	1	
6	Label 257	Adhesive, flag, 15x65 mm	1	



Notes:

Electical requirement: 1 A, 5 Vdc

Hi-Pot test: 600 Vac, 0.5 mA, 1 second



Wiring diagram		
50-00425	Wire Color	50-00030
1	Black with stripe	Sleeve
2	N.C.	-
3	N.C.	-
4	Black	Center

Revision:	Date:	Description:	Prepared:	Notes:	<h1>TENSILITY</h1> tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com
A	11/10/2009	Initial release	GL 2016.02.12 09:26:51 -08'00'		
A1	3/18/2010	Added label drawing	Verified:	Function test: no open, no short circuit, no intermittent	Size: Part number: A 10-00257
A2	9/6/2011	Updated specifications	LA <small>Digitally signed by LA, DN: cn=LA, o=Tensility, ou=Engineering, email=LA00257@tensility.com, c=US, Date: 2016.02.12 13:15:01 -08'00'</small>	Description:	
A3	8/9/2012	Added label specs and updated wire part number	Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Cable, 1830 mm, USB A plug to 2.35x0.7x9.5 mm 50-00030 plug, center neg, 22 AWG, UL2468, 30-00008	Scale: 1:1
					Sheet 1 of 1