





NOTES:

MATERIAL:

<u>5</u>.6

HOUSING: THERMOPLASTIC POLYESTER, UL94V-0 SHELL: STEEL, TIN PLATED CONTACT: COPPER ALLOY, 30µ GOLD PLATED OPERATING TEMPERATURE: -55°C to +85°C (1)

CURRENT RATING: 3A PER CONTACT CONTACT RESISTANCE: 25mΩ MAX. INSULATOR RESISTANCE: 5000MΩ min. DIELECTRIC WITHSTANDING VOLTAGE: 1000V AC rms

	628 SERIES D-SUB CONNECTOR		SW REFERENCE NO.: 628 ASSEMBLY		
			DRAWN: C.B	DATE: AUG. 01/20	018
			CHECKED: DATE:		
YOUR CO	EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: 1:1	SHEET 1 OF	1
	YOUR CONNECTION TO QUALITY & SERVICE		DRAWING NUMBER: 628-025-	622-249	ISSUE
			PART NUMBER: 628-025-	622-249	1



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR R₀HS COMPLIANCY.