	T G	יד m	C	כ	0		σ	Þ		,
4	R 22.6 Max (rel) (rel) (				<image/> <image/>	OUT SHOWN AS EXAMP	ν			4
	CHARACTERISTICS Standard : Based on MIL-DTL-38999 Series III	Keying Shown as example           Connector dimension           Dim         Nominal								
2	-Shell Material: Aluminium-Shell Plating: Black Zinc Nickel-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer-Contact Plating: Gold over copper Alloy 0.8µm minimum	A       34.9±0.3         B       19.07+0.1/-0.15         R       32.5Max         S       31.8±0.4         W       2.2+0.9/-0.1         VV THREAD       M15x1-6g			due to a use o the Specifications	ot be liable for any non- of the Products which do issued by either of the P onal recommendation, to Country FR	oes not comply wi Parties or by a thir	th d party Control List		2
	-Durability       : 500 Mating cycles         -Delivered with Souriau contacts and Accessories         -Temperature Range       : -65°C to +175°C         A       01-10-2016									-
_	-Salt Spray : 500 hours -Mass : 18.06 g ± 10%		-	A 01-10-20 ISS DATE Designed By:		n - by	CUST	OMER DRAWING	MOD N°	
	BASIC SERIES:     8D     7     -     11     Z     99       SHELL TYPE     : Jam nut Receptacle	A C	_	SCALE NA		Aluminium Ree General linear Tolerances: ±	NP	Series RDS / PROJECT <b>859</b> his document is the prop	erty of	1
	CONTACT TYPE       : Standard Crimp Contact         SHELL SIZE : 11         PLATING       : Z = Black Zinc Nickel	ORIEN CONTACT TYPE : PIN(50 CONTACT LAYO	00 Matings)	FORMAT A3	U WWW.	SOURIAU.COM	1 cor RG N°	is document is the prop SOURIAU it must not be reproduc nmunicated without per	ed or mission SHEET	-
	H G	F			С	8D711Z99A	B	Α	1/2	

ſ	Т	۵	г	п	D	0	σ	Þ	_
4	-×	Contact Layout $ \begin{array}{c}                                     $				Panel cutout	Λ.		4
	Conta positi ID A B C D E F F G Shell Arrangement Numb	X-axis (mm)         Y-axis (mm)           +.065 (1.65)         +.113 (2.87)           +.130 (3.30)         +.000 (0.00)           +.065 (1.65)        113 (2.87)          015 (1.65)        113 (2.87)          130 (3.30)         +.000 (0.00)          065 (1.65)         +.113 (2.87)          005 (1.65)         +.113 (2.87)           +.000 (0.00)         +.000 (0.00)	1			ØC	ය ₩		
ى ع	size no. cont 11 -99 7	acts contacts rating location			E	Dim         Nominal           B         19.59+0/-0.           ØC         20.96+0.25.	25		3
		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)							
2					A 01-10-2016	PN: 8E	Country Jurisdiction & FR Not I	& Control List isted	2
								-	
-					SCALE NA SOURIAU		IAU.COM	PRDS / PROJECT 859 This document is the property of SOURIAU it must not be reproduced or sommunicated without permission	
					FORMAT A3		RIAU DRG N° 711Z99AC-C	SHEET 2/2	_
_	Н	G	F	E	D	С	В	A	