

- High efficiency switching power supplies
- Easy installation into standard flush boxes
- Fully encapsulated plastic housing
- Dust and waterproof to IP 67
- Protection class II
- Safety approval to IEC/EN 60950-1, EN 50178, IEC/EN 60335-1
- Approved for mounting onto wood or materials with unknown flammability
- Ready to meet ErP directive
- Universal input range 90 to 264 VAC
- Regulated output voltage



The TIW series is a new range of small size DC-power supplies which have been designed particularly for applications in home and office installations. The compact module cases fit in the standardized in-wall flush boxes or also can be mounted on walls. The power supplies fully comply with the safety and EMC standards requested for commercial and residential class II installations. Typical applications are powering of electric devices used in home automation and in security systems like e.g. controllers, indicators, etc.

| Models | | | | | |
|------------|-------------------|---------------------|---------------------|---------------------|-----------------|
| Order Code | Output Power max. | Output Voltage nom. | Output Current max. | Output Current peak | Efficiency typ. |
| TIW 06-103 | 4 W | 3.3 VDC | 1'200 mA | 1'560 mA | 73 % |
| TIW 06-105 | 5 W | 5 VDC | 1'000 mA | 1'300 mA | 76 % |
| TIW 06-106 | 6 W | 6 VDC | 1'000 mA | 1'300 mA | 81 % |

Input Specifications

| | | |
|------------------------|--------------|---|
| Input Voltage | - AC Range | 90 - 264 VAC (Full Range) |
| | - DC Range | 130 - 375 VDC (Designed for, no certification) |
| Input Frequency | | 47 - 63 Hz |
| Power Consumption | - At no load | 300 mW max. (Ready to meet ErP directive) |
| Input Inrush Current | - At 230 VAC | 24 A max. |
| | - At 115 VAC | 12 A max. |
| Recommended Input Fuse | | 6'000 mA (slow blow) (The need of an external fuse has to be assessed in the final application.) |

Output Specifications

| | | |
|--|---------------------------------|--|
| Voltage Set Accuracy | | ±3% max. |
| Regulation | - Input Variation (Vmin - Vmax) | 1% max. |
| | - Load Variation (0 - 100%) | 2% max. |
| Output Current peak | | Boost Power: 130% of Output Current max. Duration 10 s max. Duty 10% max. |
| Ripple and Noise (20 MHz Bandwidth) | | 200 mVp-p max. |
| Minimum Load | | Not required |
| Hold-up Time | - At 230 VAC | 20 ms min. |
| | - At 115 VAC | 5 ms min. |
| Start-up Time | - At 230 VAC | 1'000 ms max. |
| | - At 115 VAC | 1'000 ms max. |
| Short Circuit Protection | | Continuous, Automatic recovery |
| Output Current Limitation | | 250% max. of Iout max. |

Safety Specifications

| | | |
|------------------|-----------------------------|--|
| Safety Standards | - IT / Multimedia Equipment | EN 60950-1 EN 62368-1 IEC 60950-1 IEC 62368-1 UL 60950-1 |
| | - Household | EN 60335-1 IEC 60335-1 |
| | - Power Installation | EN 50178 IEC 62103 |
| | - LED Modules Controlgear | EN 61347-1 EN 61347-2-13 |
| | - Luminaires for Furniture | VDE 0710-14 |
| | - Power Transformers | EN 61558-1 EN 61558-2-8 EN 61558-2-16 |
| | - Certification Documents | www.tracopower.com/overview/tiw06 |
| | Protection Class | Class I & II (Prepared): Reinforced Insulation |
| | Class 2 Power Units | UL 1310 |

All specifications valid at nominal voltage, full load and +25°C after warm-up time unless otherwise stated.

EMC Specifications

| | | |
|--------------------------------|------------------|---|
| EMI Emissions | | EN 61000-6-3 (Generic Residential) |
| - Conducted Emissions | | EN 55014-1 (internal filter) |
| | | EN 55032 class B (internal filter) |
| - Radiated Emissions | | EN 55014-1 (internal filter) |
| | | EN 55032 class B (internal filter) |
| - Harmonic Current Emissions | | EN 61000-3-2, class A |
| EMS Immunity | | EN 61000-6-2 (Generic Industrial) |
| | | EN 61204-3 (Low Voltage Power Supplies) |
| - Electrostatic Discharge | | Air: EN 61000-4-2, ± 8 kV, perf. criteria B |
| | | Contact: EN 61000-4-2, ± 4 kV, perf. criteria B |
| - RF Electromagnetic Field | | EN 61000-4-3, 3 V/m, perf. criteria A |
| - EFT (Burst) / Surge | | EN 61000-4-4, ± 0.5 kV, perf. criteria A |
| | | EN 61000-4-4, ± 2 kV, perf. criteria B |
| | | L to L: EN 61000-4-5, ± 1 kV, perf. criteria A |
| - Conducted RF Disturbances | | EN 61000-4-6, 3 Vrms, perf. criteria A |
| - Voltage Dips & Interruptions | 230 VAC / 50 Hz: | EN 61000-4-11 |
| | | 30%, 0.5 periods, perf. criteria A |
| | | 60%, 5 periods, perf. criteria B |
| | 115 VAC / 60 Hz: | EN 61000-4-11 |
| | | 30%, 0.5 periods, perf. criteria B |
| | | 60%, 5 periods, perf. criteria B |

General Specifications

| | | |
|---------------------------|-------------------------|--|
| Relative Humidity | | 100% max. |
| Temperature Ranges | - Operating Temperature | -25°C to +50°C (without derating) (Please take heat sources (such as lamps) nearby into consideration for ambient temperature of the power supply.) |
| Over Temperature | - Protection Mode | 140°C typ. (Automatic recovery) |
| Protection Switch Off | - Measurement Point | Internal IC temperature |
| Cooling System | | Natural convection (20 LFM) |
| Altitude During Operation | | 3'000 m max. |
| Insulation System | | Reinforced Insulation |
| Isolation Test Voltage | - Input to Output, 60 s | 3'000 VAC |
| Leakage Current | - Touch Current | 0.25 mA max. |
| (at 254.4 VAC / 60Hz) | | |
| Reliability | - Calculated MTBF | (Please refer to application-note.) |
| Environment | - Vibration | IEC 60068-2-6 |
| | | 5 g, 3 axis, sine sweep, 60-500 Hz |
| | - Mechanical Shock | IEC 60068-2-27 |
| | | 50 g, 3 axis, half sine, 11 ms |
| Case Ingress Protection | | IP 67 (acc. IEC 60529) |
| Housing Material | | Plastic (UL 94 V-0 rated) |
| Connection Type | | Wired |
| Weight | | 80 g |
| Environmental Compliance | - REACH Declaration | www.tracopower.com/info/reach-declaration.pdf REACH SVHC list compliant REACH Annex XVII compliant |
| | - RoHS Declaration | www.tracopower.com/info/rohs-declaration.pdf Exemptions: 6a, 6c, 7a, 7c-I, 7c-II (RoHS exemptions refer to the component concentration only, not to the overall concentration in the product (O5A rule). The SCIP number is provided on request.) |

All specifications valid at nominal voltage, full load and +25°C after warm-up time unless otherwise stated.

Supporting Documents

Overview Link (for additional Documents)

www.tracopower.com/overview/tiw06

Outline Dimensions

