

Tripp Lite

1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

# Dual-Bay USB 3.0 SuperSpeed to 2.5 in. SATA III Portable Hard Drive RAID Enclosure with UASP Support

MODEL NUMBER: **U357-025-2** 











Portable enclosure connects two 2.5 in. SATA hard drives to a single USB 3.0 port for easy access in RAID or other disk modes. UASP-enabled for 70% more speed with UASP host controller.

## Description

The U357-025-2 Dual-Bay USB 3.0 SuperSpeed to 2.5 in. SATA Portable Hard Drive RAID Enclosure is a quick, easy way to connect two SATA HDDs (Hard Disk Drive) or SSDs (Solid State Drive) to your laptop, netbook or notebook's USB 3.0 port. Not only does it support USB 3.0 data transfer rates up to 5 Gbps, but it reads data up to 70 percent faster and writes up to 40 percent faster than USB 3.0 when connected to a UASP-enabled host controller.

Perfect for portable storage or backing up system data, the compact enclosure is compatible with 2.5-inch SATA drives up to 2 TB (and will support larger drives when available). RAID 0 (mirrored drive), RAID 1 (single drive) and JBOD (dual drives) disk modes allow flexible access to your storage and are easily selectable via DIP switch. No tools are required, making the U357-025-2 an ideal choice for quick on-themove storage.

The U357-025-2 accepts SATA III, II and I drives and is backward-compatible with previous USB generations. No software, drivers or external power supply is required; connect the included USB power cable to your computer or USB charger to power on the unit. Compatible with any USB-enabled operating system.

#### **Features**

### Quickly Connects 2 SATA Drives to Your Computer's USB 3.0 Port

- Recommended for portable storage or backing up system data
- Supports USB 3.0 data transfer rates up to 5 Gbps
- Features UASP for performance up to 70% faster when connected to UASP-enabled host controller

# **Highlights**

- Supports USB 3.0 data transfer rates up to 5 Gbps
- Works up to 70% faster when connected to UASP host controller
- Compatible with 2.5 in. SATA
  HDDs and SSDs up to 2 TB
- RAID 0, RAID 1 and JBOD modes for flexible access to data
- Recommended for portable storage or backing up system data

# **System Requirements**

- Two 2.5 in. SATA HDDs or SSDs with 9.5 mm maximum height
- Device with USB port (USB 3.0 required to achieve USB 3.0 speeds)
- USB-enabled operating system
- UASP-enabled host controller required for UASP performance

# **Package Includes**

- U357-025-2 Dual-Bay USB 3.0
  SuperSpeed to SATA Portable
  Hard-Drive RAID Enclosure
- USB 3.0 A to Micro-B device cable, 2 ft.
- USB A to Micro-B power cable,
  2 ft.
- Owner's manual



• Compatible with any USB-enabled operating system

#### Compatible with 2.5 in. SATA Drives Up to 2 TB

- Accepts SATA III, II and I drives
- Backward compatible with previous USB generations
- Works with both SATA HDDs and SSDs

#### **Built for Portable Use**

- Plug and play—no software, drivers or external power supply needed
- Portable tool-free design for quick on-the-move external storage
- SATA drives slide easily into convenient trays
- Protective covers keep dust and dirt away from sensitive SATA drives
- USB 3.0 Micro-B device and USB power cables included

# **Specifications**

OVERVIEW		
UPC Code	037332200914	
Drives Supported	2.5" HDD (max height: 9mm)	
INPUT		
Bus Powered	Yes	
USER INTERFACE, ALERTS & CONTROLS		
LED Indicators	Blue (Read, Write, Power, RAID mode)	
PHYSICAL		
Shipping Dimensions (hwd / in.)	2.10 x 5.50 x 9.20	
Shipping Dimensions (hwd / cm)	5.33 x 13.97 x 23.37	
Shipping Weight (lbs.)	0.40	
Shipping Weight (kg)	0.18	
Unit Packaging Type	Вох	
Unit Dimensions (hwd / in.)	1.1 x 5.2 x 3.1	
Unit Dimensions (hwd / cm)	2.7 x 13.2 x 7.9	
Unit Weight (lbs.)	0.2	
Unit Weight (kg)	0.09	
Material of Construction	ABS	
Color	Black	





ENVIRONMENTAL		
Operating Temperature Range	50 to 122 F (10 to 50 C)	
Storage Temperature Range	32 to 149 F (0 to 65 C)	
Relative Humidity	10% to 85% RH, Non-Condensing	
BTUs	17.1 BTU/Hr	
Power Consumption (Watts)	5	
CONNECTIONS		
Ports	2	
Side A - Connector 1	USB 3.0 A (MALE); USB A (MALE)	
Side B - Connector 1	(2) 22 PIN SATA + POWER (FEMALE)	
Connector Plating	Nickel	
FEATURES & SPECIFICATIONS		
USB Specification	USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps)	
Driver Required	No	
UASP Support	Yes	
Technology	USB 3.0 (SuperSpeed); SATA/eSATA; USB	
CERTIFICATIONS		
Certifications	Tested to CE, FCC, RoHS, REACH	
WARRANTY		
Product Warranty Period (Worldwide)	3-year limited warranty	

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>