




VRR Indust X7R HVHT200C, Ceramic, 0.39 uF, 10%, 1000 VDC, X7R, Commercial, High Temperature, HighVoltage, Lead Spacing = 15.24mm



Click here for the 3D model.

| Dimensions |                    |
|------------|--------------------|
| L          | 19.05mm MAX        |
| W          | 20.32mm MAX        |
| т          | 9.52mm MAX         |
| S          | 15.24mm +/-0.76mm  |
| LL         | 3.175mm MIN        |
| F          | 0.813mm +/-0.102mm |

| Packaging Specifications |           |  |  |
|--------------------------|-----------|--|--|
| Packaging                | Bulk, Bag |  |  |
| Packaging Quantity       | 1         |  |  |

| General Information        | 1   |
|----------------------------|---|
| Series                     | VRR Indust X7R HVHT200C   |
| Style                      | Radial  |
| Description                | Commercial, High Temperature, HighVoltage                                   |
| Features                   | Commercial  |
| RoHS                       | No  |
| Prop 65                    | A WARNING: Cancer and reproductive harm -<br>http://www.p65warnings.ca.gov. |
| SCIP Number                | 8b930311-e6ed-4436-9857-2b5f449be092  |
| Termination                | Lead (SnPb)   |
| Failure Rate               | N/A   |
| Testing and<br>Reliability | Standard  |
| AEC-Q200                   | No  |

| Specifications                  |                 |  |  |  |
|---------------------------------|-----------------|--|--|--|
| Capacitance                     | 0.39 uF         |  |  |  |
| Capacitance Tolerance           | 10%             |  |  |  |
| Voltage DC                      | 1000 VDC        |  |  |  |
| Dielectric Withstanding Voltage | 1500 VDC        |  |  |  |
| Temperature Range               | -55/+200°C      |  |  |  |
| Temperature Coefficient         | X7R             |  |  |  |
| Dissipation Factor              | 2.5%1kHz1.0Vrms |  |  |  |
| Insulation Resistance           | 2.5641 GOhms    |  |  |  |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.