



基板取付穴推奨寸法

(基板厚: t=1~1.6mm)
 RECOMMENDED PC BOARD
 HOLE DIMENSION
 (THICKNESS: t=1~1.6mm)

注記
 NOTE

- △ 適合ターミナル: 50034 8*00
 APPLICABLE TERMINAL: 50034 8*00
- 2. 材料 ハウジング: ポリアミド, UL94V-0
 色: ナチュラル(白)
 MATERIAL HOUSING: POLYAMIDE, UL94V-0
 COLOR: NATURAL(WHITE)
- 3. ELV 及び RoHS 適合品
 ELV AND RoHS COMPLIANT.

18	20.4	51015 1000	10
16	18.4	0900	9
14	16.4	0800	8
12	14.4	0700	7
10	12.4	0600	6
8	10.4	0500	5
6	8.4	0400	4
4	6.4	0300	3
2	4.4	51015 0200	2
B	A	ORDER No.	極数 NO. OF CKT

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

DIMENSION UNITS	SCALE	CURRENT REV DESC: OBSOLETE PART NUMBER AS PER PCN#509988	molex		
mm	8:1	EC NO: 704776			
GENERAL TOLERANCES (UNLESS SPECIFIED)		DRWN: SUGEEB	2.0 BOARD IN CONN HSG		
10 ^{UNDER}	±0.2	CHK'D: GGA	PRODUCT CUSTOMER DRAWING		
10 ^{OVER} 30 ^{UNDER}	±0.25	APPR: GGA	DOCUMENT NUMBER		
30 ^{OVER}	±0.3	INITIAL REVISION:	SD-51015-XX00		
ANGULAR ±3°		DRWN: RFC_PLMIMP	DOC TYPE DOC PART REVISION		
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		APPR: YOITO	PSD 020 D		
		THIRD ANGLE PROJECTION	SHEET NUMBER		
		DRAWING	1 OF 1		
		SERIES			
		MATERIAL NUMBER			
		CUSTOMER			
		A3-SIZE			
		51015			
		SEE TABLE			
		GENERAL MARKET			