THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.

MATERIALS:




HOUSING: PBT, UL94V-0, BLACK COLOR INSULATOR: PBT, UL94V-0, WHITE COLOR


WIRE-HOUSING SEAL: SILICON RUBBER


ISSUE NUMBER

ORIGINAL

1








SPECIFICATIONS:

- PITCH: 2.5MM
- **RATED VOLTAGE: 250V** 3.
- RATED CURRENT: 3A MAX
- WITHSTAND VOLTAGE: AC1000V R.M.S. CONTACT RESISTANCE: 15 mOHMS MAX
- INSULATION RESISTANCE: 6.
 - 1000 MOHMS MIN/DC 500V
- TEMPERATURE RANGE: -40°C ~ +105°C WATERPROOF GRADE: TESTED AND
 - **CERTIFIED TO IP67**



ITEM NO.	DESCRIPTION	QTY.
1	565-005-000-411_Housing	1
2	565-005-000-411_Rear Insulator	1
3	565-005-000-411_Rear Gasket	1

Waterproof Connector, Insulator, Female, Black, 5Pin 565-005-000-411

EDAC INC TORONTO, ONTARIO CANADA YOUR CONNECTION TO QUALITY & SERVICE

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

CHECKED: DATE: SCALE: NOT TO SCALE SHEET 1 OF 1 DRAWING NUMBER **ISSUE** 565-005-000-411

565-005-000-411 DATE: OCT.29/10

ACAD REFERENCE NO.

DRAWN:R.STA.MONICA



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2002/95/EC AND 2002/96/EC FOR RoHS COMPLIANCY