

C0805X223K5RAC3316

SMD Auto X7R VW80808, Ceramic, 0.022 uF, 10%, 50 VDC, X7R, SMD, MLCC, Automotive Grade, 0805



Click here for the 3D model.

| Dimensions | |
|------------|-----------------|
| Chip Size | 0805 |
| L | 2mm +/-0.3mm |
| W | 1.25mm +/-0.3mm |
| Т | 0.9mm +/-0.10mm |
| S | 0.75mm MIN |
| В | 0.5mm +/-0.25mm |

Packaging Specifications

Packaging Packaging Quantity

T&R, 180mm, Plastic Tape 4000

| General Information | |
|---------------------|----------------------------------|
| Series | SMD Auto X7R VW80808 |
| Style | SMD Chip |
| Description | SMD, MLCC, Automotive Grade |
| Features | VW 80808 Specification Compliant |
| RoHS | Yes |
| Termination | Flexible Termination |
| Failure Rate | N/A |
| Qualifications | AEC-Q200 |
| AEC-Q200 | Yes |
| Shelf Life | 152 Weeks |

| Specifications | | |
|---|----------------------|--|
| Capacitance | 0.022 uF | |
| Capacitance Tolerance | 10% | |
| Voltage DC | 50 VDC | |
| Dielectric Withstanding Voltage | 125 VDC | |
| Temperature Range | -55/+125°C | |
| Temperature Coefficient | X7R | |
| Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC) | 15%, 1kHz 1.0Vrms | |
| Dissipation Factor | 2.5%1kHz 1.0Vrms | |
| Insulation Resistance | 45.4545 GOhms | |

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.