

P 469-206-4040 sales@inteliheat.com

Thermosafe Technologies LLC dba Inteliheat North America 624 Krona, Suite 115 Plano, TX 75074, U.S.A.

## InteliHeat® Thermulate® Full Coverage 55-gallon (200 Liter) Heating Jacket (HPNA/D2/OR)

Our InteliHeat® Thermulate® HPD2 Full Coverage 55-gallon Heating Jacket certified for non-hazardous ordinary locations provides increased power to reach higher temperatures in a shorter time.

- Maximum power to reach highest temperatures. Two independently controlled heating circuits.
  32-320°F(0-160°C) adjustable thermostat fitted as standard to each circuit
- Special formulated high-temperature, chemically resistant silicon-coated glass-cloth used on both sides of the jacket to extend product life in demanding applications.
- High grade thermal insulation to reduce heat loss and increase efficiency while providing protection for the operator.
- Fitted with adjustable retaining straps and quick release buckles.
- Flexible conforms to the container wall providing optimal thermal coupling
- Delivers heat over a large surface area, minimizing the possibilities of damaging the product.
- Fit and forget, built to last no regular maintenance required.
- Safe to use 24/7.
- 7 ft. (2m) premium oil, water, and abrasion resistant power cable
- Fitted with NEMA 1-15P plug
- Double insulated product
- Ideal for melting solids
- Ambient temperature: -40°F to +104°F (-40°C to +40°C)
- ETL approved to UL and CSA standards.
- Waterproof and custom sizes available.

To fit container: 55 Gallon / 200 Liter Thermostat: Adjustable 0-160°C / 0-320°F

Size: Circumference 71" – 76.75" / Height 34" (1800 – 1950mm / 864mm)

120 Volts

1300 Watts per circuit 2600 Watts total

Part Number: HPNA/D2/OR/# /EC/120/2600/0-160

