


TOLERANCE UNLESS OTHERWISE SPECIFIED		
.X	±0.25	
.XX	±0.13	

.XXX ±0.05

THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER ORIGINAL



NOTES:

MATERIAL:

HOUSING: THERMOPLASTIC POLYESTER, UL94V-0

SHELL: STEEL, TIN PLATED

CONTACT: COPPER ALLOY, GOLD FLASH PLATED

OPERATING TEMPERATURE: -55°C ~ 125°C

50Ω (IMPEDANCE)

(IF PRESENT)

SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT


SIGNAL CONTACT RESISTANCE: $10m\Omega$ MAX.

POWER/CO-AX CONTACT RATING:

INSULATOR RESISTANCE: 5000MΩ min.

DIELECTRIC

WITHSTANDING VOLTAGE: 1000V AC rms



— 11.94	
3.20	

COMBINATION D-SUB



EDAC INC TORONTO, ONTARIO CANADA

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC..AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

	SW REFERENCE NO.: 629 COMBO ASSEMBLY			
ĺ	DRAWN: C.B	DATE: JAN. 01/20	19	
	CHECKED:	DATE:		
	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2	
ĺ	DRAWING NUMBER: 620-36W/2/0-5TE		ISSLIE	

DRAWING NUMBER: 629-36W4240-5TE ISSUE PART NUMBER: 629-36W4240-5TE

TOLERANCE UNLESS OTHERWISE SPECIFIED

.X ±0.25 .XX ±0.13 .XXX ±0.05 THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER
ORIGINAL (1)

· (©O) ·

 \circ

2W2

2WK2

5W1

0000 3W3 3WK3

○ (○...O) o

11W1

○ ○ ○ ○ ○ ○ ○ ○ ○

9W4

0000000

13W3

0.....0

21W1

17W2

000000....0

000:::::0000

17W5

00000000 8W8 25W3

13W6

0 (0 :::::::::: O 0 |

000:::::000

21W4

36W4

o[.....oo)o

47W1

COMBINATION D-SUB

 SW REFERENCE NO.:
 629 COMBO ASSEMBLY

 DRAWN:
 C.B

 DATE:
 JAN. 01/2019

 CHECKED:
 DATE:

 SCALE:
 N.T.S

 SHEET
 2

 DRAWING NUMBER:
 629-36W4240-5TE

 ISSUE

THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

COMPLIANT

