

#### Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of GJM0225C1E8R2BB01# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=GJM0225C1E8R2BB01%23

"#" indicates a package specification code.

## GJM0225C1E8R2BB01L













< List of part numbers with package codes > GJM0225C1E8R2BB01L



### **Applications**

Unsuitable	Please be sure to read and comply with
Applications	these "Precautions for use."
Applications  Specific Applications	these "Precautions for use."  Consumer equipment, Industrial Equipment, Mobile Electronics, Medical equipment [GHTF A/B/C] except for implant equipment, Automotive infotainment/comfort equipment Please refer to Our Website and specifications, etc. for information about the performance, functions, quality, management, and safety required for the above applications, and use Products after confirming the
	performance and reliability of the actual Product.



#### References

Packaging	Specifications	Standard Packing Quantity
L	180Embossed Tape	40000

Mass (typ.)	
1 piece	0.09mg



# Appearance & Shape





1 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





# GJM0225C1E8R2BB01L

Note: This datasheet may be out of date.

Please download the latest datasheet of GJM0225C1E8R2BB01# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=GJM0225C1E8R2BB01%23

"#" indicates a package specification code.



## **Specifications**

Length	0.4±0.02mm	
Width	0.2±0.02mm	
Thickness	0.2±0.02mm	
Capacitance	8.2pF ±0.1pF	
Distance between external terminals g	0.13mm min.	
External terminal size e	0.07 to 0.14mm	
Operating Temperature Range	-55°C to 125°C	
Rated Voltage	25Vdc	
Size code in inch(mm)	01005 (0402M)	
тс	0±30ppm/°C	
Temperature characteristics	COC(EIA)	
(complied standard)	C0G(EIA)	
Temperature range of	25°C to 125°C	
temperature characteristics	25 € 10 125 €	

2 of 2

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

