

6

5

4

3

2

1

E

E

D

D

C

C

B

B

A

A

F3 MAX-LOC NUT

STAINLESS STEEL
SCREWS W/FLAT
WASHER 1 $\frac{1}{2}$ "
AND O-RINGSTAINLESS STEEL
SCREWS W/LOCK
WASHER
(6) REQ'DSTAINLESS STEEL
SUPPORT RINGS
(2) REQ'DMAINTAINED ON/OFF
(505SW-N)

YELLOW BUTTON PILOT LIGHT (505PL-YB)

RED BUTTON PILOT LIGHT (505PL-RB)

BLANK (505BLNK)

GREEN BUTTON PILOT LIGHT (505PL-GB)

E-STOP RED, MAINTAINED (505B-RM)

BLANK (505BLNK)

14.50"

(1.18")
BETWEEN CENTERS

(3.52")

(2.31")

NOTES:

1. INSTALLATION INSTRUCTIONS, BUTTON ID. LABELS. ARE PACK WITH THE PART.
2. ALL BUTTONS ARE HIGH AMBIENT, CHEMICALLY RESISTANT MATERIAL - COLOR BLACK

RELEASE DRAWING EC NO: WNA2011-0412 DRWN: HKNEELAN 2011/02/09 CHKD: HKNEELAN APPR: DTITUS 2011/03/22	QUALITY SYMBOLS $\nabla=0$ $\sphericalangle=0$	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE IN/MM		SCALE NTS	DESIGN UNITS INCH	THIRD ANGLE PROJECTION		
		4 PLACES	mm	INCH	DRAWN BY HKNEELAN	DATE 2011/02/09	TITLE 5058 W/505SW-N, YELLOW RED & GREEN PILOT BUTTON E-STOP IN POS #7			
		3 PLACES	\pm --	\pm .005	CHECKED BY HKNEELAN	DATE 2009/02/09	MOLEX INCORPORATED			
		2 PLACES	\pm 0.13	\pm 0.10	APPROVED BY DTITUS	DATE 2011/03/22	MATERIAL NO. 1301260330	DOCUMENT NO. SD-130126-047	SHEET NO. 1 OF 1	
A	REV	ANGULAR $\pm 1/2^\circ$		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				

6

5

4

3

2

1