Mo 08-	unting Option #4-40 Unified Threaded Inserts	<u>Contact Detail</u> 500-Wire Hole .087x.013(2.21x0.33) - Tail LG.=.282(7.16) .156 [3.96] Contact Spacing x .140 [3.56] Row Spacing	THIS IS A C.A.D. GENERATE DO NOT MAKE MANUAL REV	D DRAWING ISIONS TO MAS	STER.	ISSUE NUM ORIGINA	
	Card Slot Accepts054 (1.37) to .070 (1.78) Thick P.C. Board			1			
\\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\							
	0.156[3.96]	6.248[158.70]					
	-	6.394[162.41] ————————————————————————————————————	▶				
						49] Slot	
						0.295 [7.49] Card Slot	
	A						
1]	<u>↓</u>	-'	
					0.090[2.29]		
460[11.68]		6.990[177.55]	D[177.55]		t of Contact	ECTION	1 A-A
0.460			305 / 315 / 355 Card Edge Connector Part Number: 305-078-500-208		ACAD REFERENCE 1 DRAWN: J.LEE CHECKED:	DATE: SEI	NG MASTER PT. 21/09
	See Accompanying Page for: Mounting Options	EDAC TORONTO, CANA	ONTARIO ARE THE PROPERTY OF ED SHALL NOT BE REPRODUCE	AC INC.,AND ED,OR COPIED OR THE	SCALE: NTS DRAWING NUMBER	SHEET	1 OF 2
		YOUR CONNECTION TO QUALITY &	SERVICE WITHOUT WRITTEN PERMISS		305 Assembl	у	1

