

TOLERANCEUNLESS OTHERWISESPECIFIED.X±0.25.XX±0.13.XXX±0.05

THIS IS A C.A.D. GENERATED DRAWING

DO NOT MAKE MANUAL REVISIONS TO MASTER.

> THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

COMPLIANT

## NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:


THERMOPLASTIC POLYESTER, UL94V-0 STEEL, TIN PLATED COPPER ALLOY, GOLD FLASH PLATED

OPERATING TEMPERATURE:

POWER/CO-AX CONTACT RATING:40A (CURRENT)(IF PRESENT)SIGNAL CONTACT CURRENT RATING:5A PER CONTACTSIGNAL CONTACT RESISTANCE:10mΩ MAX.

INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE:

1000V AC rms



				SW REFERENCE NO.: 630 COMBO ASSEMBLY						
		COMBINATION D-SUB DRAWN: C.B DATE: JAN. 01/2019   CHECKED: DATE:   EDAC INC THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC., AND SCALE: (IN C.A.D. 1:1) SHEET 1 OF 2								
					CHECKED:			DATE:		
	YOUR CONNECTION TO	TORONTO, ONTARIO CANADA		SCALE:	(IN C.A.D. 1:	1)	SHEET	1	OF	2
				DRAWING NUMBER: 630-24W7			7250-4T2			ISSUE
Y				PART NUM	BER:	630-24W7	250-4T2			1

-55°C ~ 125°C

5000MΩ min.



(1)



