7					
		4			
LAYOUT SHOWN AS EXAMPLE		3			
Keying Shown as example					
CHARACTERISTICS Connector dimension					
-Standard : Based on MIL-DTL-38999 Series III Dim Nominal					
Sell Material : Aluminium ØS 25 Max -Shell Plating : Nickel Z 31 Max -Insulator : Thermoplastic VV THREAD M15x1-6g -Contacts : Copper Alloy : Silicon Elastomer . -Seals & Grommet : Sold over copper Alloy 0.8µm minimum . .					
ability : 500 Mating cycles vered with Souriau contacts and Accessories					
-Temperature Range -65°C to +200°C -Salt Spray : 48 hours A 15-10-2016 First Release					
Mass : 14.47 g ± 10%	MOD N°				
Designed By: Date: CUSTOMER DRAWIN TITLE Aluminium Plug 8D series	<u> </u>	_			
→ BASIC SERIES: 8D 5 - 11 F 22 A A S SHELL TYPE : Plug with RFI Shielding - 11 F 22 A A S SHELL TYPE : Plug with RFI Shielding - 11 F 22 A A S		-			
CONTACT TYPE : Standard Crimp Contact ORIENTATION : A SHELL SIZE : 11 CONTACT TYPE : PIN(500 Matings)	J oduced or				
PLATING : F = Nickel CONTACT LAYOUT : 11-22 FORMAT SOURIAU DRG N°	SHEET	_			
A3 SOOKIAO DKG N 8D511F22AA-C	1/2				
	A				

-	Ŧ	۵	п –	m	D	0
4		Contact Layout 22*				
	Ctc	4#22D 11-22 X Y]			
ω	A B C D	1.905 1.905 1.905 -1.905 -1.905 -1.905 -1.905 1.905				
						SOURIAU shall not be liable for a due to a use of the Products v the Specifications issued by either (professional recommend
Ю						Coun
					A 15-10-201 ISS DATE Designed By:	PN: 8D511 6 First Release Latest modification - by Date:
					TITLE	Alumi
<u> </u>					SCALE NA	General linear Tolerances:
					SOURIAU	WWW.SOURIAU.
					FORMAT	SOURIAU

G

Н

F

Е

A3

D

С

