ATGBICS FTLX1871D3BCL Finisar Compatible Transceiver SFP+ 10GBase-ZR (1550nm, SMF, 80km, LC, DOM)

Brand: ATGBICS Product code: FTLX1871D3BCL-C

Product name : FTLX1871D3BCL Finisar Compatible Transceiver SFP+ 10GBase-ZR (1550nm, SMF, 80km, LC,

DOM)

ATCHICS ATTRIBOGOSSLAND

Re of the analysis and analysis analysis and analysis analysis and analysis analysis and analysis analysis analysis analysis analysis and analysis analysi

FTLX1871D3BCL Finisar Compatible Transceiver SFP+ 10GBase-ZR (1550nm, SMF, 80km, LC, DOM)

ATGBICS FTLX1871D3BCL Finisar Compatible Transceiver SFP+ 10GBase-ZR (1550nm, SMF, 80km, LC, DOM):

ATGBICS FTLX1871D3BCL 10GBase-ZR supports a distance of up to 80km over single mode fibre (SMF) using a wavelength of 1550nm via an LC connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of Finisar FTLX1871D3BCL= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.



Performance		Power	
SFP transceiver type * Fiber optic Maximum data transfer rate * 10000 Mbit/s Interface type * SFP+ Single-mode fiber (SMF) supported ✓	Input voltage Maximum voltage Power consumption (typical)	3.3 V 3.5 V 1.5 W	
	•	Operational conditions	
Multi-mode fiber (MMF) supported Fiber optic connector SFP transceiver standard Maximum transfer distance Wavelength Ethernet LAN	c connector LC ceiver standard ZR stransfer distance 80000 m stth 1550 nm LAN sinterface type 10 Gigabit Ethernet	Minimum operating temperature Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	-5 °C 70 °C -5 - 70 °C -40 - 85 °C 0 - 95% 0 - 95%
Digital Diagnostics Monitoring		Weight & dimensions	
(DDM)	✓	Width	13.4 mm
Wavelength-division multiplexing (WDM)	×	Depth Height	56.5 mm 8.5 mm
Features		Weight	19 g
Product colour Housing material Plug and Play	Silver Metal ✔	Packaging data Number of products included Package type	1 pc(s) Box
Hot-Plug support	1	Technical details	
Hot-swap Easy to install Country of origin	√ √ China	Sustainability compliance Sustainability certificates	√ RoHS
Brand compatibility Certification	Finisar CE, FCC, RoHS	Doesn't contain	Lead



5056468761576

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.