

## Type 1 Mild Steel 3 Piece Flushmount Enclosure N1W F Series

**Hinge Door with Quarter Turn** 









### **Application**

- Designed for indoor use to enclose controls, instruments, and components which do not require oil-tight or dust-tight protection.
- Ideal for applications where components may be easily mounted and wired prior to installation of wrapper and door.

#### **Standards**

- UL 50 Type 1
- CSA Type 1
- · Complies with
  - o NEMA Type 1
  - o IEC 60529, IP20

#### Construction

- Three piece assembly consisting of a base, wrapper, and door.
- · Components are attached and secured with metal screws.
- 14 gauge reverse formed base acts as mounting surface (no separate inner panel) and provides clearance for mounting hardware.
- Punched for left or right hinging of the door and ease of assembly.
- Wrapper is formed from 16 gauge steel, with no knock-outs in the sides.
- Flush mounting door assembly formed from 16 gauge steel.
- Door is fastened with a slotted quarter turn latch.
- A bonding stud is provided on the door and a grounding screw is provided for the enclosure.

#### **Finish**

• Base, wrapper and door are finished in ANSI 61 gray powder coating.

#### **Accessories**

Type 1 Lock Kit

Padlock Adaptor

# New and improved PDF part drawing files with more detail now available.

Click part number in table below to access PDF, DXF, and STEP files.

	Enclosure			
Part No.	Н	W	D	
N1WF864	8.00	6.00	4.00	

		Enclosure		
Part No.	Н	W	D	
N1WF1084	10.00	8.00	4.00	
N1WF12104	12.00	10.00	4.00	
N1WF16124	16.00	12.00	4.00	
N1WF20164	20.00	16.00	4.00	
N1WF24204	24.00	20.00	4.00	

Data subject to change without notice

© 2021. Hammond Manufacturing Ltd. All rights reserved.