# Caps for Holder FEU (Grip)



250 VAC · 4 W / 10 A (VDE) · 600 VAC/DC · 20 A (UL/CSA)

See below:

**Approvals and Compliances** 

#### References

Mating Cap to FEU (Grip)

#### Weblinks

pdf data sheet, html datasheet, General Product Information, Packaging details, Distributor-Stock-Check, Detailed request for product, Microsite

#### **Technical Data**

| 5 x 20 or 6.3 x 32 mm              |
|------------------------------------|
| 250 VAC (VDE), 600 VAC/DC (UL/CSA) |
| 10A (VDE), 20A (UL/CSA)            |
| 4W / 10A @ Ta 23°C                 |
| IP 40                              |
| -40 °C to 85 °C                    |
| Thermoplastic, UL 94V-0            |
| 0°C to 60°C, max. 70% r.h.         |
|                                    |

# **Approvals and Compliances**

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in Details about Approvals

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

#### **Product standards**

Product standards that are referenced

| Organization | Design                | Standard             | Description  |
|--------------|-----------------------|----------------------|--|
| <u>IEC</u>   | Designed according to | IEC 60127-6          | Miniature fuses. Part 6. Fuse-holders for miniature fuse-links |
| (UL)         | Designed according to | UL 4248-1            | Fuseholder general requirements                                |
| CSA<br>Group | Designed according to | CSA C22.2 no. 4248.1 | Fuseholder general requirements                                |

# **Application standards**

Application standards where the product can be used

| Organization | Design                         | Standard     | Description   |
|--------------|--------------------------------|--------------|---|
| <u>IEC</u>   | Designed for applications acc. | IEC/UL 60950 | IEC 60950-1 includes the basic requirements for the safety of information technology equipment. |

# Compliances


The product complies with following Guide Lines


| Identification | Details    | Initiator   | Description   |
|----------------|------------|-------------|---|
| ROHS           | RoHS       | SCHURTER AG | Directive RoHS 2011/65/EU, Amendment (EU) 2015/836  |
| <b>©</b>       | China RoHS | SCHURTER AG | The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.  |
| REACH          | REACH      | SCHURTER AG | On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force. |

**-**129.5 mm









Variant 0031.1812 Variant 0031.1811

### **All Variants**

| Сар        | Fuse-Link  | Degree of Protection | Order Number | _ |
|------------|------------|----------------------|--------------|---|
| Fingergrip | 6.3 x 32mm | IP40                 | 0031.1812    | ı |
| Fingergrip | 5 x 20mm   | IP40                 | 0031.1811    |   |

Most Popular.

Availability for all products can be searched real-time:https://www. schurter.com/en/Stock-Check/Stock-Check-SCHURTER

**Packaging Unit** 

Plastic Bag (100 pcs.)

information. All content is subject to modifications and amendments. Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability and test each

product selected for their own applications.