




# 00X8020E026

110 Delta Drive  
 Pittsburgh, PA 15238  
 NAFTA Sales: (1)800-245-3984  
 HK Sales : (852)3102-9337  
 magnetics@spang.com  
 www.mag-inc.com



XFlux Permeability ( $\mu$ )	$A_L$ (nH/T <sup>2</sup> )	Core Marking	
		Lot Number	Part Number
26	103 $\pm$ 8%	XXXXXX	X8020E026

	Dimensions		Tolerance ( $\pm$ )			Packaging
	(mm)	(in)	(mm)	(in)		
<b>A</b>	80.01	3.149	1.19	0.047		Box Qty= 72 Pcs
<b>B</b>	38.10	1.499	0.64	0.025		
<b>C</b>	19.81	0.780	0.38	0.015		
<b>D</b>	28.02	1.103	-	-	<b>Min</b>	Available Hardware
<b>E</b>	59.28	2.333	-	-	<b>Min</b>	00B8020B1
<b>F</b>	19.81	0.780	0.38	0.015		00B8020B2
<b>L</b>	9.91	0.390	-	-	<b>Nom</b>	
<b>M</b>	19.81	0.780	-	-	<b>Min</b>	

Electrical Characteristics			Physical Characteristics					
Watt Loss @ 50kHz, 100mT max (mW/cm <sup>3</sup> )	DC Bias min (oersteds)		Break Strength Min (kg)	Window Area $W_a$ (mm <sup>2</sup> )	Cross Section $A_e$ (mm <sup>2</sup> )	Path Length $L_e$ (mm)	Volume $V_e$ (mm <sup>3</sup> )	Est. Weight (Ea. Piece) (g)
500	80%	50%	39	1,110	389	185	72,000	230
	195	340						

Notes:	Temperature Rating
	Curie Temp: 700 °C

