Mounting Option Contact Detail .128 (3.25) Dia. Side Mounting Holes Wire Hole .087x.013(2.21x0.33) - Tail LG=.282(7.16) .156 [3.96] Contact Spacing x .200 [5.08] Row Spacing 0.156 [3.96] 0.500[12.70] 6.092[154.74] --6.238 [158.45]


THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER

ORIGINAL





-6.524 [165.71]

-6.834[173.58]

YOUR CONNECTION TO QUALITY & SERVICE

EDAC INC TORONTO, ONTARIO CANADA

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC., AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

ACAD REFERENCE NO. 307 ENG MASTER DRAWN: DATE: AUG. 11/09 J.LEE CHECKED: DATE: SCALE: SHEET OF 3 DRAWING NUMBER **ISSUE** 307 Assembly

.175 [4.45] Point of Contact (FROM BTM OF SLOT)

Card Slot Accepts .054 [1.37] to .070 [1.78] Thick P.C. Board

SECTION A-A

See Accompanying Pages for:

- **Contact Bend Details**
- **Mounting Options**

0.473[12.01]



