

NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED COPPER ALLOY, 15µ GOLD PLATED

(1)


OPERATING TEMPERATURE: -55°C TO +85°C


CURRENT RATING: CONTACT RESISTANCE: **INSULATOR RESISTANCE:** DIELECTRIC

3A PER CONTACT $25m\Omega$ MAX. 5000MΩ min.

WITHSTANDING VOLTAGE: 1000V AC rms

637 SERIES D-SUB CONNECTOR		SW REFERENCE NO.: 637 ASSEMBLY				
		DRAWN: C.B		DATE: AUG. 01/2018		
		CHECKED:		DATE:		
EDAC INC TORONTO, ONTARIO CANADA ECTION TO QUALITY & SERVICE	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: 1:1		SHEET 1	OF	1
		DRAWING NUMBER: 637-026-330-041			ISSUE	
		PART NUMBER:	637-026-3	330-041		1







THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

