<u>م</u> ا			0	Ξ	Þ	
ØS-						
	,		LAYOUT SHOWN AS	EXAMPLE		
	Keying Shown as example					
CHARACTERISTICS	Connector dime					
-Standard : Based on MIL-DTL-38999 Series III -Shell Material : Aluminium		Nominal 32.5 Max				
-Shell Plating : Olive drab Cadmium	Z VV THREAD	31 Max M22x1-6g	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with			
-Insulator : Thermoplastic			the Specifications issued by either of the Parties or by a third party			
-Contacts : Copper Alloy			(professional recommend	lation, technical notice.)		
-Seals & Grommet : Silicon Elastomer			Cour	ntry Jurisdiction & Cont	trol List	
-Contact Plating : Gold over copper Alloy 0.8µm minimum			FI	R Not Listed		
-Durability : 500 Mating cycles			PN: 8D515W05PE			
-Delivered with Souriau contacts and Accessories						
-Temperature Range <u>-65°C to +175°C</u>		A 19-10-	-2016 First Release			
-Salt Spray : 500 hours		ISS DA	TE Latest modification - by		MOD N°	
Mass : 26.04 g ± 10%		Designed By:	Date:	CUSTOME	R DRAWING	
		TITLE	TITLE Aluminium Plug 8D series			
BASIC SERIES: 8D 5 - 15 W	05 P E	SCALE	General linear		PROJECT	
		NA			59	
SHELL TYPE : Plug with RFI Shielding					cument is the property of	
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 15		ORIENTATION : E T TYPE : PIN(500 Matings)	AU WWW.SOURIAU		SOURIAU It not be reproduced or	
SHELL SIZE . 15					icated without permission	
			CALIDIA		SHEET	
PLATING : W = Olive drab Cadmium	<u> </u>	CONTACT LAYOUT : 15-05		U DRG N° N05PE-C	1/2	

	Ŧ	۵	г	m	D	0
4		Contact Layout $ \begin{array}{c}  & & \\$				
		Location           X-axis         Y-axis           (mm)         (mm)           +.000 (0.00)         +.100 (2.54)           +.174 (4.42)         +.024 (0.61)           +.094 (2.39)        148 (3.76)          094 (2.39)        148 (3.76)				
ω						
2						SOURIAU shall not be liable for an due to a use of the Products w the Specifications issued by either o (professional recommenda Count FR
					A 19-10-20	PN: 8D515
					ISS DATE Designed By:	Latest modification - by Date:
					TITLE	Alumir
<u> </u>					SCALE NA	General linear Tolerances: ±
					SOURIAU	U WWW.SOURIAU.C
					FORMAT A3	SOURIAU 8D515W
	Н	G	F	E	D	С

