


| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A   | 43,8              |
| B   | 1 1/2-18NEF-2A    |
| C   | 27,6              |
| D   | 53                |


| NO. | BESCHREIBUNG / DESCRIPTION              |
|-----|---|
| 2   | ISOLIERKÖRPER BUCHSE / INSULATOR SOCKET |
| 3   | DICHTKÖRPER / GROMMET                   |
| 4   | ENDRING / ENDRING                       |
| 6   | KONTAKTBUCHSE / CONTACT SOCKET          |
| 7   | ZYLINDERGHÄUSE / BARREL                 |
| 9   | ÜBERWURFMUTTER / COUPLING NUT           |
| 10  | DICHRING FRONT / FRONT SEALING RING     |
| 20  | KURZES ENDGEHÄUSE / SHORT ENDBELL       |



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.  
 Specification and Dimensions subject to change  
 Drawings illustrate normal insulator positioning

| Material Specification: |                                |
|-------------------------|--------------------------------|
| Shell Material:         | Aluminium alloy                |
| Shell Plating:          | Black Zinc Cobalt (conductive) |
| Insulator Material:     | Neoprene                       |
| Contact Material:       | Copper alloy                   |
| Contact Plating:        | Hard silver                    |

all dimensions are in mm  
 Dimensions without tolerance indications are general tolerances in acc. with DIN7168m  
 drawing for  
 CUSTOMER

|  |  |                        |
|--|--|------------------------|
| <br>ITT<br><i>Engineered for life</i><br>ITT CANNON GmbH<br>D - 71384 Weinstadt/Germany | description  | CA3106R24-28S-F80-A206 |
|  | Plug, straight<br>Shortened light-weight endbell without cable clamp<br>AWG Crimp / Socket / Layout: 24-28 |                        |

© All rights reserved. Reproduction or issue to third in any form  
 whoever is only permitted with written authorization of ITT Cannon

|      |                |
|------|----------------|
| page | revision       |
| 1/1  | 929 11. Jun 19 |