

VGA Monitor Y Splitter Cable (HD15 M/2xF), 1 ft. (0.31 m)

MODEL NUMBER: P516-001





Highlights

- Splits the VGA/XVGA signal providing simultaneous display of the same image on two monitors
- HD15 Male splits to 2 HD15 Female

System Requirements

 PC/MAC with 15-pin Female VGA CPU port

Package Includes

 1-ft. (0.31 m) VGA/XVGA Splitter Cable

Description

Tripp Lite's 1-ft. (0.31 m) VGA/XVGA Monitor "Y" Splitter cable provides an inexpensive alternative for splitting the video signal from your PCs VGA port to two monitors (up to 800 x 600) that use standard 15-pin plugs. Perfect for laptops to display on a separate, larger monitor. Use for short distance applications only. For higher resolution monitors, use P516-001-HR. For applications that require longer distances and highest resolution, see Tripp Lite B114-002-R, powered 2-Port Splitter, or, B114-004-R, powered 4-Port Splitter.

Features

- HD15 Male to 2 x HD15 Female w/Hex Nuts
- Molded, double-shielded construction for maximum EMI/RFI protection
- Two monitors display the image from one PC
- Inexpensive solution for presentations

Specifications

OVERVIEW		
UPC Code	037332123602	
Product Type	Splitter	
Technology	VGA/SVGA	
Host Connector	HD15 (MALE)	
Cable Type	Passive	
PHYSICAL		
Color	Black	



Cable Jacket Color	Black	
Cable Length (ft.)	1	
Cable Length (m)	0.30	
Cable Length (in.)	12	
Shipping Dimensions (hwd / in.)	0.25 x 6.30 x 7.50	
Shipping Dimensions (hwd / cm)	0.64 x 16.00 x 19.05	
Shipping Weight (lbs.)	0.30	
Shipping Weight (kg)	0.14	
CONNECTIONS		
Side A - Connector 1	HD15 (MALE)	
Side B - Connector 1	(2) HD15 (FEMALE)	
Latching or Gripping Connector	No	
Input x Output	1 x 2	
Daisy-chainable / Cascadable	No	
FEATURES & SPECIFICATIONS		
MST Support	No	
IP68 Rated	No	
STANDARDS & COMPLIANCE		
Product Compliance	RoHS	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	Lifetime limited warranty	



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.