## ATGBICS XFP-10GZR-OC192LR Cisco Compatible Transceiver XFP 10GBase-ZR (1550nm, SMF, 80km, DOM)

## Brand : ATGBICS

Product code: XFP-10GZR-0C192LR-C

Product name : XFP-10GZR-OC192LR Cisco Compatible Transceiver XFP 10GBase-ZR (1550nm, SMF, 80km, DOM)

## XFP-10GZR-OC192LR Cisco Compatible Transceiver XFP 10GBase-ZR (1550nm, SMF, 80km, DOM)


ATGBICS XFP-10GZR-OC192LR Cisco Compatible Transceiver XFP 10GBase-ZR (1550nm, SMF, 80km, DOM):

ATGBICS XFP-10GZR-OC192LR XFP10GBase-ZR supports a distance of up to 80km over single mode fibre (SMF) using a wavelength of 1550nm via an LC connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of XFP-10GZR-OC192LR= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.





Performance		Features	
SFP transceiver type *Fiber opticMaximum data transfer rate *10000 Mbit/sInterface type *XFPSingle-mode fiber (SMF) supported✓Multi-mode fiber (MMF) supportedXFiber optic connectorLCSFP transceiver standardZRMaximum transfer distance80000 mWavelength1550 nmEthernet LAN✓Ethernet interface type10 Gigabit EthernetDigital Diagnostics Monitoring (DDM)✓	10000 Mbit/s	Certification	CE, FCC, RoHS
		Power	
	✓ × LC ZR 80000 m 1550 nm ✓ 10 Gigabit Ethernet	Input voltage Maximum voltage Power consumption (typical) Operational conditions Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions	3.3 V 3.5 V 1.5 W 70 °C 0 - 70 °C -40 - 85 °C 0 - 95% 0 - 95%
Wavelength-division multiplexing (WDM)	×	Width	18.5 mm
Features Product colour Housing material	Silver Metal	Depth Height Weight	71 mm 8.5 mm 36 g
Plug and Play	√	Packaging data	
Hot-Plug support Hot-swap	4	Number of products included Package type	l pc(s) Box
Easy to install	1	Technical details	
Country of origin United Kingdom Brand compatibility Cisco	United Kingdom Cisco	Sustainability compliance Sustainability certificates Doesn't contain	✔ RoHS Lead



5056468713490

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.