-	Σ	G	П	m	D	0	σ	А	
4	R 22.6 Max			S		<image/> <image/>	EXAMPLE		4
	CHARACTERISTICS		Keying Shown as	s example Connector dimension					
N	-Standard : Based on MIL-DTL-38999 Set -Shell Material : Aluminium -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastor -Contact Plating : Gold over cop -Durability : 500 Mating cy -Delivered with Souriau contacts and A	c mer oper Alloy 0.8µm minimun ycles	n	DimNominalA58.7±0.3B42.85+0.1/-0.15R32.5MaxS55.6±0.4W3+0.9/-0.1VV THREADM37x1-6g		SOURIAU shall not be liable for due to a use of the Products the Specifications issued by either (professional recommend Court F PN: 8D72	which does not comply wit of the Parties or by a third dation, technical notice.) htry Jurisdiction & R Not Lis	th d party Control List	2
	-Temperature Range : -65°C to +200 -Salt Spray : 48 hours -Mass : 97.56 g ± 10%				ISS DATE Designed By:	6 First Release Latest modification - by Date:		MOI DMER DRAWING	D N°
_ <b>_</b>	BASIC SERIES: 8   SHELL TYPE : Jam nut Receptacle 1   CONTACT TYPE : Standard Crimp Con 1   SHELL SIZE : 25 1   PLATING : F = Nickel 1		F 43 S C	ORIENTATIO CONTACT TYPE : SOCKET(500 Mat CONTACT LAYOUT : 2		General linea Tolerances: ± WWW.SOURIAU SOURIA	.COM	SERIES RDS / PROJECT 859 is document is the property of SOURIAU t must not be reproduced or municated without permission SHE 1/	ET
L	Н	G	F	E	D	C	B	A	]

ſ	D I	П	m		0	₿ >		7
4	Contact Layout		Panel cutout JAM NUT RECEPTACLE (TYPE 7)					
	$\begin{array}{ c c c c c c c c c c c c c c c c c c c$	Y-axis (mm) 531 (13.49) 344 (8.74) 172 (4.37)			ØC			
ω	$\begin{array}{c c c c c c c c c c c c c c c c c c c $	172 (4.37) 344 (8.74) 344 (8.74) 172 (4.37) 172 (4.37) 172 (4.37) 172 (4.37) 172 (4.37) 172 (4.37)			DimNominalB43.43+0/-0.25ØC44.7+0.25/-0			3
	size no. contacts contacts rating location	upersedes 520057-43						
					SOURIAU shall not be liable for any due to a use of the Products whic the Specifications issued by either of t (professional recommendation)	ch does not comply with the Parties or by a third party		
N					Country FR	Jurisdiction & Control List Not Listed		2
					PN: 8D725F43SC			
				A 03-10-2016 F	First Release			
				ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING	MOD N°	
		TITLE Aluminium Receptacle 8D series				Receptacle 8D series		
				SCALE	General linear	NPRDS / PROJECT		_
<u> </u>					Tolerances:	859	roporty of	1
		SOURIAU WWW.SOURIAU.COM This document is the SOURIAU it must not be reprint to communicated without it must not be reprint to the communicated without it must					uced or	
				FORMAT A3	SOURIAU 8D725F4		SHEET	
Į	H G	F	E	D	C	B A		