

CM031005 SPECIFICATIONS

Holder: HC-45/U

Frequency: See Table

Mode: Fundamental

Load Capacitance: TBD

Frequency stability: ± 150 ppm, -15° to 175°C with respect to nominal frequency.


Series Resistance: 25 ohms Max.

Reference HC-45/U Cold Weld Small Footprint Outline drawing for dimensions.

A sample of crystals from each production run shall be subjected to vibration in accordance with MIL-STD-202, Method 204, Test Condition D except the frequency range shall be 10 Hz to 500 Hz. The change in operating frequency of the crystals shall not exceed 5 ppm, and the change in series resistance shall not exceed 10%.

Part Number	Frequency	Motional Capacitance
CM031005-12	12.000 MHz	12.0 pF
CM031005-16	16.000 MHz	16.0 pF
CM031005-18	18.432 MHz	18.0 pF
CM031005-25	25.000 MHz	20.0 pF

Crystals are manufactured for high temperature operation up to 175°C : holder, leads, and electrodes are Gold plated. Polyimide cement is used internally.

APPROVALS	NAME	INITIALS	DATE	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES. TOLERANCES: FRACTIONS 2 - PLACE 3 - PLACE ANGLES DECIMALS DECIMALS $\pm 1/64"$ $\pm 0.020"$ $\pm 0.005"$ $\pm 1/2^{\circ}$		
DRAWN						
ENGINEERING MANAGER						
PRODUCTION MANAGER						
QUALITY ASSURANCE						
		DRAWING NUMBER CM031005		REV.		
Fundamental Mode High Temperature AT-Cut Crystal						
VI CINOX 4914 Gray Road - Cincinnati, OH 45232		FSCM NUMBER 58997	SCALE	DATE ISSUED 3/23/2005	SIZE A	SHEET 1 OF 1