

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: 3.1TYPE-C connector male 24P vertical three-legged without hook	
	Model No. Connector	Part No./Ordering No. PLUG-USBC-241SMTV-4BQC13

In Addition to GlobTek Inc.'s renewed ISO9001:2008 - Quality Management System Certification, GlobTek Inc. is now certified to:

ISO13485:2003 - Medical Devices Quality Management System Certification
ISO14001:2004 - Environmental Management System Certification

ISO Certificates are available online at <http://www.globtek.com/iso-certificates/>

The acceptance of this specification and use of the product described in this document indicates the acceptance and binding of the customer to Globtek TERMS AND CONDITIONS (attached to the end of this document), which supersede all other agreements, terms, and conditions (<http://en.globtek.com/terms-and-conditions/>).

Prop 65 Statement:<https://en.globtek.com/prop-65-statement.pdf>

Footnote:

GlobTek Inc. will not be liable for the safety and performance of these power supplies if unauthorized access and repair occurs. End user should consult applicable UL, CSA or EN standards for proper installation instruction.

Limitation of Use:

GlobTek products are intended for use with commercial, medical, and/or industrial equipment only. GlobTek product are not authorized for use as mission critical components in life support hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of GlobTek Inc.

Contents of this document are subject to change without prior notice.

Customer Approval of Specification:

Please approve, sign and send back to GlobTek so we can complete order processing.
A delay in receipt of this form will delay delivery schedule.

Company Name:	Customer P/N:
Quote Number:	Date:
Authorized Representative Name:	Authorized Representative Signature:

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: 3.1TYPE-C connector male 24P vertical three-legged without hook	
	Model No. Connector	Part No./Ordering No. PLUG-USBC-241SMTV-4BQC13
		Rev B

REVISION HISTORY

REV	DESCRIPTION	SUB	DATE	APPROVED
B	Update drawing	QA	04/28/2023	QA
A	Initial release	QA	07/20/2022	QA

3D CAD FILE:

<https://www.globtek.com/file/dl/plug-usbc-241smtv-4bqc13.stp>

AGENCY ONLINE DOCUMENTS


RoHS/RoHS3 Declaration https://www.globtek.com/pdf/rohs_cert/01t3a000005hQlhAAE

REACH Declaration https://www.globtek.com/pdf/iso_certificates/REACH.pdf

Conflict Minerals Declaration <https://www.globtek.com/pdf/conflict-minerals.pdf>

Prop 65 Statement <https://en.globtek.com/prop-65-statement.pdf>

IPXY rating is based on 3rd party testing and customers should check suitability and test system level IPXY rating before ordering.



PLUG-USBC-241SMTV-4BQC13

PROPRIETARY INFORMATION

PROPRIETARY OF GLOBTEK, INC. ANY REPRODUCTION, DISCLOSURE OR USE OF THIS DRAWING, IN WHOLE OR IN PART, IS HEREBY PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBTEK, INC. © GlobTek, Inc. 2022 - 2023

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: 3.1TYPE-C connector male 24P vertical three-legged without hook	
	Model No. Connector	Part No./Ordering No. PLUG-USBC-241SMTV-4BQC13
		Rev B

5	COVER	HIGH TEMPERATURE PLASTIC	LCP BLACK	1PCS
4	SPRING	STAINLESS STEEL	----	2PCS
3	LATCH	STAINLESS STEEL	TiN: 80-120u"/Min/Ni base 50u"/Min Plated	1PCS
2	SHELL	STAINLESS STEEL	Ni 50u"/Min Plated	1PCS
1	TERMINAL HOUSING	HIGH TEMPERATURE PLASTIC	LCP BLACK/CONTACT Au 1u"/Min Ni base 50u"/Min	2PCS
No.	DESCRIPTION	MATERIAL	REMARKS	QTY

A1	GND	B12	GND
A2	SSTXP1	B11	SSRXP1
A3	SSTXN1	B10	SSRXN1
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	DP1	B7	DN2
A7	DN1	B6	DP2
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A10	SSRXN2	B3	SSTXN2
A11	SSRXP2	B2	SSTXP2
A12	GND	B1	GND
PIN	SIGNAL NAME	PIN	SIGNAL NAME





NOTES:

SPECIFICATION:


1. CURRENT RATING: 3.0 MAX
2. VOLTAGE: 100VAC
3. TEMPERATURE RANGE: -30C ~ 85C
4. CONTACT RESISTANCE: 40MILLIONHM MAX
5. INSULATION RESISTANCE: 100 MEGA OHMS MIN.
6. INSERTION FORCE: 5N ~ 20N
7. UNMATING FORCE: 8N ~ 20N
8. DURABILITY: 10,000CYCLES

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: 3.1TYPE-C connector male 24P vertical three-legged without hook	
	Model No. Connector	Part No./Ordering No. PLUG-USBC-241SMTV-4BQC13


PACKING:



NOTES
 1. 帶子引導長度
 LEAD TAPE LENGTH
 拉線方向
 PULL OUT DIRECTION



2. 上帶 剝力為: 0.1~1.3N(10.2gf~130gf)
 PEELING OFF FORCE OF TOP TAPE: 0.1~1.3N(10.2gf~130gf)
 出貨運輸過程中一定注意:
 THIS REQUIREMENT SHOULD BE APPLIED AT SHIPMENT:
 非帶在運輸過程中不能脫膠
 PEELING OFF SHOULD NOT BE ALLOWED DURING TRANSPORTATION



Temperature Life, Vibration, Cyclic Temperature and Humidity, Thermal Shock, Mixed Flowing Gas and etc.:
<https://www.globtek.com/pdf/ENVIRONMENTAL.pdf>

GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: 3.1TYPE-C connector male 24P vertical three-legged without hook	
	Model No. Connector	
	Part No./Ordering No. PLUG-USBC-241SMTV-4BQC13	Rev B



GlobTek, Inc. www.globtek.com 186 Veterans Drive, Northvale, NJ 07647 Tel. (201) 784-1000 Fax (201) 784-0111	Drawing Title: 3.1TYPE-C connector male 24P vertical three-legged without hook	
	Model No. Connector	Part No./Ordering No. PLUG-USBC-241SMTV-4BQC13
		Rev B

PACKAGING

Packing Spec P/N: _____

Box Qty: 3000

Gift Box Size (mm): _____

Gift Box Color: White

Master Carton Size (mm): 340 x 340 x 220

Master Carton Cubic

Volume (m³): 0.03

Master GW (Kg): 6.0 kg

wt Ea. (Kg): 0.00 kg

wt Ea. (Kg): 0.00 kg

LABEL SPECS: _____ , _____

PACK SPEC: _____