

## Specification Sheet

Part Number: 157-00036



Wide Strap Cable Tie with 8mm Stud Mount, 15.7" Long, .5" Wide, PA66HIRHSUV, Black, 300/Bag

|                     |   |
|---------------------|---|
| Article Number      | 157-00036   |
| Type                | WSR8MM  |
| Color               | Black (BK)  |
| Features & Benefits | <ul style="list-style-type: none"><li>•Mount provides low insertion and high extraction forces which makes for a strong and easy installation.</li><li>•Tie utilizes a strong hinge between the stud mount and strap head to provide superior holding ability.</li><li>•Clamping rails increase grip on round bundles.</li><li>•Thinner strap provides increased flexibility for improved ergonomics.</li></ul> |
| Quantity Per        | bag   |

### Product Description

The Wide Strap Stud Mount Cable Tie minimizes pinching on soft bundles and features a low profile head to provide compact bundling. A thinner strap provides increased flexibility for improved ergonomics. Available in various stud mount sizes, the wide strap tie utilizes a strong hinge between the stud mount and head to provide superior holding ability on a threaded stud.

**Short Description**

Wide Strap Cable Tie with 8mm Stud Mount, 15.7" Long, .5" Wide, PA66HIRHSUV, Black, 300/Bag

**Global Part Name**

WSR8MM-PA66HIRHSUV-BK

**Minimum Tensile Strength (Imperial)**

120

**Minimum Tensile Strength (Metric)**

534

**Length L (Imperial)**

15.7

**Length L (Metric)**

398.8

**Fixation Method**

Weld Stud Fixing

**Identification Plate Position**

none

**Releasable Closure**

No

**Tie Closure**

plastic pawl

**Variant**

Inside Serrated

**Width W (Imperial)**

0.5

**Width W (Metric)**

12.7

**Bundle Diameter Min (Imperial)**

0.38

**Bundle Diameter Min (Metric)**

9.5

**Bundle Diameter Max (Imperial)**

4.1

**Bundle Diameter Max (Metric)**

104.1

**Stud Diameter (Metric)**

M8

**Stud Diameter (Imperial)**

5/16

**Material**

Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)

**Material Shortcut**

PA66HIRHSUV

**Flammability**

UL 94 HB

**Operating Temperature (Metric)**

-40°F to +230°F (-40°C to +110°C)

**Reach Complaint(Article 33)**

Yes

**ROHS Complaint**

Yes

**Package Quantity(Imperial)**

300

**Package Quantity (Metric)**

300

**Customs Number**

3926909988

**Content Unit(BMEcat)**

pcs.

