


a YAGEO company

C276CC25100AA0J

C27, Film, Film/Foil Polypropylene, Motor Run, 10 uF, 5%, 470 VAC



General Information Series C27 Dielectric Film/Foil Polypropylene Style Plastic Case and Cover, Ultra Sonically Welded Description Ultra Sonically Welded Seal, Safety Class PO, Features UL 94 V0 Disk **RoHS** Yes Lead Fast On (1+1) UL, VDE, UL (Construction Only), UL_94 VO Qualifications Disk AEC-Q200 No Component 52 g Weight

Click here for the 3D model.

Dimensions	
D	35mm +1mm
L	56.5mm +/-2mm

Packaging Specifications	
Mounting	Bolt-M8x20
Packaging	Bulk, Bag

Specifications			
Capacitance	10 uF		
Capacitance Tolerance	5%		
Voltage AC	470 VAC		
Temperature Range	-25/+85°C		
Rated Temperature	85°C		
Max dV/dt	15 V/us		

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.