



FEATURES

- CO₂, humidity and temperature measurement
- Dual wavelength NDIR CO₂ sensor (Non-Dispersive Infrared) for superior stability.
- User operated CO₂ calibration
- Data Hold & Max/Min/STEL/TWA function
- Adjustable auto power off timer
- Internal CO₂ alarm buzzer
- Backlight display function
- Datalogging up to 32,000 sets
- USB interface ,PC software included

SPECIFICATIONS

Measurement Range: CO ₂ : 0 ~ 30000 ppm Temperature: 0 to 50°C (32 to 122°F) Humidity: 0 ~ 100%RH
Accuracy: CO ₂ : ± (75 ppm + 3% of reading) (0 ~ 5000 ppm) Temperature: ± 1.0°C Humidity: ± 4.5%RH
Resolution: 1 ppm, 0.1°C/0.1°F, 0.1%RH
Response Time: 20 seconds
Power Source: 9V alkaline battery or Micro USB
Battery life: Approximately 10 hours normal use (alkaline battery)
Operating Condition: 0°C to 50°C(< 90%RH)
Storage Condition: -20°C to 60°C(< 75%RH)
Dimensions: 226.5 x 65 x 38.5 mm
Weight: 273 g
Accessories: 9V Battery · Instruction Manual · micro USB cable · Windows software · Carrying case.

★ **NEW!**



LED Back Light



CENTER[®]
CENTER TECHNOLOGY CORP.

4F, No.415, Jung-Jeng Road, Shu-Lin Dist.,
 New Taipei City 238, Taiwan
 TEL: 886-2-26763926 E-Mail: center@centertek.com
 FAX: 886-2-26763925 http: //www.centertek.com

* The specifications and other information in this catalogue are subject to change without prior notice.

Distributed by: