## ATGBICS CWDM-SFP10G-1590-40 Cisco Compatible Transceiver CWDM SFP+10GBase (40km, SMF, LC 1590nm, DOM)

Brand : ATGBICS

Product code: CWDM-SFP10G-1590-40-C

Product name : CWDM-SFP10G-1590-40 Cisco Compatible Transceiver CWDM SFP+10GBase (40km, SMF, LC 1590nm, DOM)

CWDM-SFP10G-1590-40 Cisco Compatible Transceiver CWDM SFP+10GBase (40km, SMF, LC 1590nm, DOM)

ATGBICS CWDM-SFP10G-1590-40 Cisco Compatible Transceiver CWDM SFP+10GBase (40km, SMF, LC 1590nm, DOM):

ATGBICS CWDM-SFP10G-1590-40 10GBase CWDM supports a distance of up to 40km over single mode fibre (SMF) using a wavelength of 1590nm via an LC connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of CiscoCWDM-SFP10G-1590-40= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.





Performance		Features	
SFP transceiver type *Fiber opticMaximum data transfer rate *10000 Mbit/sInterface type *SFP+Single-mode fiber (SMF) supported✓Multi-mode fiber (MMF) supportedXFiber optic connectorLC	10000 Mbit/s	Certification	CE, FCC, RoHS
		Power	
	×	Input voltage Maximum voltage Power consumption (typical)	3.3 V 3.5 V 1 W
SFP transceiver standard	CWDM	Operational conditions	
Maximum transfer distance 40000 m   Wavelength 1590 nm   Coarse Wavelength Division ✓   Multiplexing (CWDM) ✓   Ethernet LAN ✓   Ethernet interface type 10 Gigabit Ethernet   Digital Diagnostics Monitoring ✓	Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	70 °C 0 - 70 °C -40 - 85 °C 0 - 95% 0 - 95%	
	al Diagnostics Monitoring   Image: Constant State St	Weight & dimensions	
(DDM) Features Product colour		Width Depth Height Weight	13.4 mm 56.5 mm 8.5 mm 19 g
Plug and Play		Packaging data	
Hot-swap Easy to install		Number of products included Package type	1 pc(s) Box
Country of origin Brand compatibility		Technical details	
		Sustainability compliance Sustainability certificates	✔ RoHS

Doesn't contain

Lead



5056468715029

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.