## **HellermannTyton**

## **Specification Sheet**

Part Number: 166-90907

External Metric thread provides a secure connection.

Snap-on construction reduces installation time and costs by eliminating the need to thread fittings onto conduits.

All-around "teeth" attach firmly to conduit and deliver a high extraction force.

Durable nylon material has high resistance to salts, oils, weak acids and solvents.

IP68 fitting has additional conduit seal for increased protection against wind, dirt, and water.



HelaGuard Non-Metallic IP68 Fitting, 90-Elbow, M25 Thread, 0.75" Dia, PA66, Black, 10/pkg

Article Number 166-90907

**Type** HGL075-90-M25

Color Black (BK)

Quantity Per pack

Product Description HelaGuard Non-Metallic 90-Degree Elbow fitting features a snap-on

design that provides a quick, secure connection. Constructed of a very durable nylon material with a high resistance to salts, oils, weak acids and solvents. Designed for easy removal with a small

screwdriver. IP68 ingress protection rated fittings.

**Short Description** HelaGuard Non-Metallic IP68 Fitting, 90-Elbow, M25 Thread, 0.75" Dia, PA66, Black, 10/pkg **Global Part Name** HGL075-90-M25-PA66-BK 2.60 Length L (Imperial) Length L (Metric) 66 Material Polyamide 6.6 (PA66) **Material Shortcut** PA66 **Operating Temperature** -58°F to +275°F (-50°C to +135°C) **ROHS Compliant** Yes Package Quantity (Imperial) 10

Package Quantity (Metric)

**Customs Number** 

10

3926909988