			0	₿ >]
A						4
			LAYOUT SHOWN AS EXAM	PLE		3
	Keying Shown as example					
CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III	Connector dimension Dim Nominal]				
-Shell Material : Aluminium -Shell Plating : Black Zinc Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minimum	ØS 41.7 Max Z 31 Max VV THREAD M31x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) Country Jurisdiction & Control List FR Not Listed			2
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories			PN: 8D521Z39			
-Temperature Range : -65°C to +175°C		A 12-10-201	5 First Release			-
-Salt Spray : 500 hours 		ISS DATE	Latest modification - by		MOD N°	
		Designed By:	Date:	CUSTOMER DRAWING		
		TITLE Aluminium Plug 8D ser		n Plug 8D series		
→ BASIC SERIES: 8D 5 - 21 Z 3 SHELL TYPE : Plug with RFI Shielding	9 S E	SCALE	General linear Tolerances:	NPRDS / PROJECT 859		
CONTACT TYPE : Standard Crimp Contact			WWW.SOURIAU.COM	it must not be reprodu	uced or	
SHELL SIZE : 21 PLATING : Z = Black Zinc Nickel	CONTACT TYPE : SOCKET(50 CONTACT LAYO			communicated without p	SHEET	_
	CONTACT LAY	A3	SOURIAU DI 8D521Z39		1/2	
			X115 / 1 / 2 U		1/2 1	

